

9619-9819

Max. 40,8 W




AC/DC SWITCH MODE PLUG-IN

tech spec

9819 - medisinsk godkjent / medical approved (EN 60601)
12V / 24V version



- Faste utgangsspenninger
- Spesielt konstruert for IT-utstyr
- Utskiftbare DC plugger
- Tilgjengelig i 120 V versjon
- Fixed output voltages
- Specially designed for IT-equipment
- Exchangeable DC plugs
- Available in 120 V version



9819

Tekniske data - 13,2 V versjon 9619	Technical specifications - 13,2 V version 9619
Inngangsspenning:	Input voltage: 190-264 VAC / 240-360 VDC 120V: 90+130VAC/127-180 VDC
Utgangsspenning: • Innvendig justerbar:	Output voltage: • Internally adjustable: 13,2 ± 0,1 VDC 10,0 - 15,0 V
Maks. utgangseffekt:	Max. output power: 36 W
Maks. laststrøm:	Max. load current: 2,4 A
Lastregulering:	Load regulation: < 20 mV
Linjeregulering:	Line regulation: < 20 mV
Svitsjefrekvens:	Switch frequency: 40 kHz
Temperaturområde:	Temperature range: -10°C - +40°C
Rippel:	Ripple: < 30 mV p-p 40 kHz/100 Hz
Strømbegrensning:	Current limiting: Min. 2,6 A, max. 3,1 A
Overspenningsbeskyttelse:	Overvoltage protection: Zener
Isolasjonsklasse:	Insulation class: II
Elektrisk sikkerhetsstandard:	Electrical safety standard: EN 60065, EN 60950
EMC standarder • Emisjon: • Immunitet:	EMC standards • Emission: EN 61000-6-3 • Immunity: EN 61000-6-1
Utgangsterminaler • Sek. ledning med/uten plugg:	Output terminals • Cord with/without plug: Tilbehør / Accessories
Mål uten plugg (LxBxH):	Dimensions without plug (LxWxH): 100 x 63 x 47 mm

Visse tekniske data kan variere for de forskjellige modeller og spenningsversjoner.
Some technical specifications may differ for other models and voltage versions.

Spenningsversjoner 9619 - Voltage versions 9619

Inngang (VAC) Input (VAC)	Utgang (VDC) Output (VDC)		Maks. strøm (A) Max. current (A)	Maks. utgangseffekt (W) Max. output power (W)
	Nom. Nom.	Innvendig justerbar Internally adjustable		
230	7,5	4,5 - 7,8	3,0	23,4
230	9	7,5 - 12,0	2,8	33,6
120* / 230	13,2	10,0 - 15,0	2,4	36
230	18,2	15,0 - 24,0	1,7	40,8
230	24,4	24,0 - 30,0	1,3	39

- * UL godkjent (UL 1950)
- * UL approved (UL 1950)

28122007