

OB BB 10 7

Origin - Provenance - Provenienza : C.E.E.



STRUCTURE

SEAT

Anatomical support in (11 mm thickness) of beech plywood with threaded metal inserts.

PADDING

SEAT

Cold injected Polyurethane foam, CFC free, 40 kg/m³ density, 60 mm thickness.

UPHOLSTERY

SEAT

Symil-leather/Fabric stiched and mounted to the load-bearing support.

CONNECTION

Seat/backrest through 30x15 oval tube (15/10 thickness), painted with black epoxy powders.

MECHANISMS TILTING

Tilting mechanism lockable in all positions by means of a lever located under the left-hand side of the seat.

SEAT HEIGHT ADJUSTMENT

Through a class 3 gas lift with 200 mm stroke, complying with DIN 4550/4551 standards



OB BB 10 7

Origin - Provenance - Provenienza : C.E.E.

BASE

5-star base in black nylon reinforced, Ø 650 mm.

OPTIONAL

5-star base in die-cast, brushed aluminium with chromium plated effect Ø 650 mm.

FEET


Fixed polypropylene feet, Ø 70 mm.

OPTIONAL

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair, Ø 50 mm.

CASTORS

Black soft castors with grey rubber for hard floor and wooden.



DIMENSIONS - INGOMBRI

| | | | |
|---|-----------------|-----|--------|
| A | Seat height | Min | 530 mm |
| | | Max | 730 mm |
| C | Seat width | | 480 mm |
| D | Max total width | | 640 mm |
| E | Seat depth | | 310 mm |
| F | Total depth | | 640 mm |

WEIGHT 6,70 Kg

VOLUME 0,08 m3

Quantity per Box N. 1

HOBBIT



OB BB 10 9

Origin - Provenance - Provenienza : C.E.E.



STRUCTURE

SEAT

Anatomical support in (11 mm thickness) of beech plywood with threaded metal inserts.

PADDING

SEAT

Cold injected Polyurethane foam, CFC free, 40 kg/m³ density, 60 mm thickness.

UPHOLSTERY

SEAT

Symil-leather/Fabric stiched and mounted to the load-bearing support.

CONNECTION

Seat/backrest through 30x15 oval tube (15/10 thickness), painted with black epoxy powders.

MECHANISMS TILTING

Tilting mechanism lockable in all positions by means of a lever located under the left-hand side of the seat.

SEAT HEIGHT ADJUSTMENT

Through a class 3 gas lift with 260 mm stroke, complying with DIN 4550/4551 standards

FOOTREST

Footrest in nylon fiberglass reinforced, Ø 450 mm, manually adjustable in height by means of a knob.



OB BB 10 9

Origin - Provenance - Provenienza : C.E.E.

BASE

5-star base in black nylon reinforced, Ø 650 mm.

OPTIONAL

5-star base in die-cast, brushed aluminium with chromium plated effect Ø 650 mm.

FEET


Fixed polypropylene feet, Ø 70 mm.

OPTIONAL

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair, Ø 50 mm.

CASTORS

Black soft castors with grey rubber for hard floor and wooden.



DIMENSIONS - INGOMBRI

| | | | |
|---|--------------------|-----|--------|
| A | Seat height | Min | 620 mm |
| | | Max | 880 mm |
| C | Seat width | | 480 mm |
| D | Max total width | | 640 mm |
| E | Seat depth | | 310 mm |
| F | Total depth | | 640 mm |
| P | Diameter foot-rest | | 450 mm |



WEIGHT 7,00 Kg

VOLUME 0,08 m3

Quantity per Box N. 1

HOBBIT

