

CE

Meets EU Safety, Health and Environmental Protection Requirements



Characteristics









Included

Ideal for housekeeping and general cleaning





- For the safe collection of combustible dusts in ordinary locations/areas and unclassified zones
- Ignition source safe/protected
- Protected against ingress of dust IP5X
- Very high level of protection inside the collection tank
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- For dry recovery only
- Disposable collection bag (conductive) included
- Stainless steel tank Type 430 fits any application
- Filter blockage indicator light
- Includes a complete static dissipative tool kit

Specifications

2D-10 (4W) HEPA ORDLOC SERIES	113185B	113185B-BLSD
Model Name	2D-10 (4W) HEPA ORDLOC SERIES	2D-10 (4W) HEPA ORDLOC BLSD SERIES
Type (Powerhead)	Electric	Electric
Tension	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz
Phase	Single	Single
Wattage	1200 W	1100 W
Power	1.2 kW	1.1 kW
Amperage	5 A	8 A
Air Flow	194 m ³ /h	215 m ³ /h
Vacuum Pressure	2504 mm H ₂ 0	2250 mm H ₂ 0
Sound Level	75 dB(A)	75 dB(A)
Type of Power Outlet	European	European
Suction Inlet	60 mm	60 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Dry Recovery - Disposable Filter Bag	19 L	19 L
Length	48 cm	48 cm
Width	46 cm	46 cm
Height	86 cm	86 cm
Cord Length	10 m	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Conductive Recovery Bags - included



Static Conductive Toolkit - Included