



## LIEBHERR THS 70 D-K - 110 D-K

Type	THS 70 D-K	THS 110 D-K	THS 140 D-K
Max. concrete output (rod side)	65 m³/h	102 m³/h	135 m³/h
Max. concrete output (piston side)	45 m³/h	62 m³/h	82 m³/h
Max. concrete pressure (rod side)	80 bar	75 bar	55 bar
Max. concrete pressure (piston side)	120 bar	125 bar	95 bar
Pump cycles (rod side)	30/min	38/min	38/min
Pump cycles (piston side)	21/min	23/min	23/min
Conveying cylinder Ø mm x stroke	180 x 1400	200 x 1400	230 x 1400
Stroke volume / double stroke	71 l	88 l	116 l
Max. hydraulic pressure	320 bar	320 bar	320 bar
Engine power	4-Zyl. / 95 kW	6-Zyl. / 145 kW	6-Zyl. / 145 kW
Hopper capacity	600 l	600 l	600 l
Total weight	7000 kg	7300 kg	7330 kg
Drive cylinder	110/63×1400	125/80×1400	125/80×1400
Water tank	500 l	500 l	500 l
Water pump	20 bar	20 bar	20 bar
Oil tank	350 l	350 l	350 l
Speed	2,6 km/h	2,6 km/h	2,6 km/h
Noise emission level	126 dB	126 dB	126 dB

Subject to technical modifications.

