

**3-gang Cambridge roller with hydraulic unfolding, with ISOBAR system- cast diameter 530-600 mm**

**Category: Soil cultivation » Rollers**

**Product code: 9459A/9467/9459N/9466N**



1



2



3



4



5

**STANDARD EQUIPMENT:**

- Hitch cross shaft cat II and III
- Cambridge cast Ø 530 mm (4 spoke)
- Central axle Ø 70 mm for cast Ø 530 mm, swivel bearing sets
- Hydraulic folding and unfolding
- Hydraulic flow divider allows evenly unfolding side sections
- Hydraulic accumulator on main cylinder circuit ensures an even weight distribution to each sections
- ISOBAR hydraulic system which ensures evenly pressure distribution on sides and ground contour following
- Mechanical transport lock
- Transport width less than 3 m
- 2 section hydraulic (4-hoses), for option with hydraulic leveling bar 3 section (6-hoses)
- Tires 400/60 - 15.5
- Wheels chocks

**OPTIONAL EQUIPMENT:**

- Cambridge cast Ø 600 mm , 3- spoke- axle Ø 65 mm
- Cutter cast Ø 520 mm
- Ø 610 mm pipe for water filling - smooth roller
- Lower drawbar pivoting hitch Ø 50 mm
- Upper drawbar hitch Ø 40 mm
- Hitch cross shaft cat. III and IV
- Hydraulic leveling board with working depth and angle adjustment
- 2-circuit pneumatic brake

**3-gang Cambridge roller with hydraulic unfolding, with ISOBAR system- cast diameter 530-600 mm**

**Category: Soil cultivation » Rollers**

**Product code: 9459A/9467/9459N/9466N**

- Hydraulic brake
- Hand brake
- Warning plates with LED lights
- Stone boxes (2 pcs)

Ref.No	Working width /m/	Number of rings /pcs/	Power demand /HP/	Weight /kg/
Cambridge ø 530 mm				
9459N	6,3	127	112-130	3350
9466N	8,3	167	120-140	4350
Cambridge ø 600 mm				
9459A	6,3	121	112-130	3900
9467	8,3	157	120-140	4950

Spring levelling board with hydraulic adjustment:

Ref.No	Type	Working width /m/	Number of tines /pcs./	Weight /kg/
9422H	hydraulic	6,3	28	415
9424H	hydraulic	8,3	36	525