Generator set data sheet



Model: C44 D5e (B3.3)

Frequency: 50 Hz
Fuel type: Diesel

Spec sheet:	S-6282-EN
Noise data sheet (open):	MSP-3025
Airflow data sheet:	MCP-2021

	Standby			Prime				
Fuel consumption	tion kVA (kW) kVA (kW)		kVA (kW)					
Ratings	44 (35)	44 (35)			40 (32)			
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
US gph	1.1	1.5	2.3	2.7	1.0	1.4	2.2	2.7
L/hr	4.0	5.7	8.8	10.4	3.9	5.4	8.4	10.2

	Standby	Prime	
Engine	rating	rating	
Engine manufacturer	Cummins		
Engine model	4BTAA3.3-G14		
Configuration	Inline, 4-Cylinder Diesel		
Aspiration	Turbocharged and after-cooled		
Gross engine power output, kWm	62.6	58	
BMEP at set rated load, kPa	1538	1428	
Bore, mm	95		
Stroke, mm	115		
Rated speed, rpm	1500		
Piston speed, m/s	5.75		
Compression ratio	19:1		
Lube oil capacity, L	8		
Overspeed limit, rpm	1650		
Regenerative power, kW	N.A.		
Governor type	Mechanical as standard		
Starting voltage	12V DC		

Fuel flow

Maximum fuel flow, L/hr	45
Maximum fuel inlet restriction, mm Hg (clean filter)	101.6
Maximum fuel inlet temperature, °C	70

Air	Standby Rating		Prime Rating	
Combustion air, m³/min	4.92		4.47	
Maximum air cleaner restriction, kPa	2.5	-		
Exhaust				
Exhaust gas flow at set rated load, m ³ /min	13.02	11	1.63	
Exhaust gas temperature, °C	497	49	492	
Maximum exhaust back pressure, kPa	10			
Standard set-mounted radiator cooling				
Ambient design, °C @ 12.7mm H ₂ O	55			
Fan load, KW _m	2 +/- 1			
Coolant capacity (with radiator), L	10.3			
Cooling system air flow, m3/sec @ 12.7mm H ₂ O	1.611			
Total heat rejection, BTU/min	1877 1734		734	
Maximum cooling air flow static restriction mm H ₂ O	25.4			
Weights*	Open	Enclosed		
Unit dry weight kg (Standard skid)	922	1236		
Unit wet weight kg (Standard skid)	1010	1414		
Unit dry weight kg (Optional skid)	1140	1543		
Unit wet weight kg (Optional skid)	1228	1631		
Dimensions	Length	Width	Height	
Open set dimensions (Standard skid)	2050	967	1510	
Enclosed set dimensions (Standard skid)	2270	975	1920	
Open set dimensions (Optional skid)	2270	967	1720	
Enclosed set dimensions (Optional skid)	2270	975	2115	

See your distributor for more information.

Cummins Power Generation

Manston Park, Columbus Avenue

Manston, Ramsgate

Kent CT12 5BF, UK

Telephone: +44 (0) 1843 255000 Fax +44 (0) 1843 255902 E-mail: cpg.uk@cummins.com Web: www.cumminspower.com





power.cummins.com

Our energy working for you.™


Genset outline


Open set





Enclosed set





Outlines are for illustrative purposes only. Please refer to the genset outline drawing for an exact representation of this model.

©2012 | Cummins Power Generation Inc. | All rights reserved | Specifications subject to change without notice | Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. PowerCommand and "Our energy working for you." are trademarks of Cummins Power Generation. Other company, product, or service names may be trademarks or service marks of others. Document no. DS374-CPGK-RevA - 24/2/2012

Alternator data

Connection ¹	Temp rise °C	Duty ²	VoltageAlternator	
Wy e -3 phase	163/125	S/P	UC122 4C	380-415
Wy e -3 phase	150/105	S/P	UC122 4D	380-415

See your distributor for more information.

Cummins Power Generation

Manston Park, Columbus Avenue

Manston, Ramsgate Kent CT12 5BF, UK

Telephone: +44 (0) 1843 255000

Fax +44 (0) 1843 255902 E-mail: cpg.uk@cummins.com Web: www.cumminspower.com



power.cummins.com

Our energy working for you.™

©2016 Cummins Power Generation Inc. All rights reserved.

Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. PowerCommand, AmpSentry, InPower and "Our energy working for you." are trademarks of Cummins Power Generation. Other company, product, or service names may be trademarks or service marks of others. Specifications are subject to change without notice.

Ratings definitions

Emergency Standby Power (ESP)	Limited-Time running Power (LTP):	Prime Power (PRP)	Base Load (Continuous) Power (COP)
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789 and DIN 6271.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	accordance with ISO 8528. Ten percent ov erload capability is	Applicable f or supplying power continuously to a constant electrical load f or unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789 and DIN 6271.

Formulas for calculating full load currents:

Single phase output

kWxSinglePhaseFactorx1000 Voltage

Three phase output

kWx1000

Voltagex1.73x0.8

See your distributor for more information.

Cummins Power Generation Manston Park, Columbus Avenue Manston, Ramsgate Kent CT12 5BF, UK

Telephone: +44 (0) 1843 255000 Fax +44 (0) 1843 255902 E-mail: cpg.uk@cummins.com

Web: www.cumminspower.com



©2016 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. PowerCommand, AmpSentry, InPower and "Our energy working for you." are trademarks of Cummins Power Generation. Other company, product, or service names may be trademarks or service marks of others. Specifications are subject to change without notice.

D-6279-EN



power.cummins.com