

Indoor & Digital Transfer



## Industrial High Quality Dye Sub Printer

The robust & industrial ValueJet 1948WX (1910 mm – 75.19”) dye sublimation printer will be a top choice for production oriented customers and businesses looking for a high quality volume printer for intensive use.

Ideal for established businesses looking for a high volume production printer, the compact & surprisingly user-friendly ValueJet 1948WX is suited for your high-end roll-to-roll sublimation needs. The printer will deliver a top speed up to 195 m<sup>2</sup>/h.

The VJ-1948WX model features 4 variable drop 8-channel print heads mounted in a staggered configuration, allowing a complete range of output resolutions between 360 x 360 dpi and 1440 x 1440 dpi.


## Product Highlights

- Transfer sublimation printing up to 1910 mm (75.19”)
- Typical production speeds between 48 & 90 m<sup>2</sup>/h
- Staggered head setup with 4 latest generation 1440 nozzle print heads
- Incorporated heaters to remove moisture from the output
- Pressure rollers with integrated disable function
- Minimum waste - individual head cleaning
- Environmentally friendly printing
- Mutoh water-based dye sublimation inks

## Application Possibilities

Grow your business with high volume dye sub applications such as high quality sportswear, in-store & personalised home textile decoration and deco fabrics, fashion, soft signage, textile banners, sports equipment and solid object decoration (ceramic, metal, wood).






Made in Japan




Piezo Variable Drop




Intelligent Interweaving



75" Wide



Four Heads



## 75" Dye Sublimation Printer

### Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Heads	4 (staggered setup)
Nozzle Configuration	180 nozzles x 8 lines / head
Drop Mass Range (pl)	5.9 - 45.3
Head Heights	Low: 1.5 mm / Middle: 2.5 mm / High: 4.0 mm

### Media Specifications

Max. Media Width	1910 mm (75,19")
Max. Print Width	1900 mm (74,80")
Max. Media Thickness	0.3 / 1.3 / 2.8 mm *
Media Measurements *	Ø 150 mm / 2" & 3" / 100 kg

\* : Max. media thickness is specified per head height

\* : Standard motorised unwinding / winding system

### Ink Specifications

Ink Type	DS2-series Water-based Universal Transfer Sublimation inks
Ink Volume	1000 ml bottle
Typical Ink Consumption	< 5 ml/m <sup>2</sup> on transfer paper
Ink Colours	CMYK
UV durability	3 to 6 months outdoor
Light fastness - ISO 105-B02(*)	C (5-6) / M (6-7) / Y (6-7) / K (6)
Washing fastness - ISO 105-C02(*)	C (4-5) / M (4-5) / Y (4-5) / K (4-5)
Perspiration fastness - ISO 105-E02(*)	C (4-5) / M (5) / Y (4-5) / K (4-5)

\* : Score Ranges (min-max) : Light 1-8 / Washing 1-5 / Perspiration (1-5)

### Performance

Super Fine (1080 x 1080 dpi 9p bi*)	22 m <sup>2</sup> /h
High Quality (720 x 1080 dpi 6p bi*)	31 m <sup>2</sup> /h
Quality Production (360 x 720 dpi 4p bi*)	48 m <sup>2</sup> /h
Production (360 x 1080 dpi 3p bi*)	62 m <sup>2</sup> /h
Selected Production (360 x 720 dpi 2p bi*)	90 m <sup>2</sup> /h
Maximum Speed (360 x 360 dpi 1p bi*)	195 m <sup>2</sup> /h

\* : bi : heads print as the carriage moves in both directions

### Power Consumption

During Printing Heaters Off	< 600 W
During Printing Heaters On	< 2840 W
Power Supply	AC 100-120 V / AC 200-240 - 60/50 Hz

### Recommended Working Environment

Temperature	22°C - 30 °C with Δt: max. 2 °C/h
Humidity	40% - 60 % (no condensation) with ΔRH: max. 5% RH/h

### Machine Measurements


Width x Depth x Height	2983 x 996 x 1261 mm
Weight	201 kg



Extended dual section heater to remove all moisture from the output before take-up/roll-up



Pressure rollers can be easily and individually disabled to cope with media cockling



Dual staggered head setup / head height up to 4 mm

Distributed by

**id.**  
**numérique**