



1



2



3



4

**STANDARD EQUIPMENT:**

- 3-point linkage cat. II or III
- Campbell casts Ø 700 mm, blade angle 30°, weight 31 kg, axle Ø 55 mm
- Swivel bearing sets
- Hydraulic folding for transport position
- Hydraulic 2-hoses connection (with leveling board 4-hoses)
- Transport width less than 3,5 m

**OPTIONAL EQUIPMENT:**

- Hydraulic leveling board with working depth and angle adjustment
- Cleaning scrapers
- Cambridge cast Ø 450 mm
- Cambridge cast Ø 500 mm
- Cambridge cast Ø 530 mm
- Cambridge cast Ø 600 mm
- Cam roller Ø 500 mm
- Crosskill cast Ø 510 mm
- Cutter cast Ø 520 mm
- Warning plates with LED lights



**zagroda**  
AGRICULTURAL TECHNIQUE

**Campbell roller front-rear mount  
and hydraulic folding**

Category: Soil cultivation » Rollers  
Product code: 9505/9510/9511/9512

Ref.No	Working width /m/	Number of rings /pcs/	Power demand /HP/	Weight /kg/
9505	4,0	25	110-130	1510
9510	6,0	37	160-190	1860
9511	4,5	29	120-140	1600
9512	5,0	31	130-160	1700

ZAGRODA.EU