

(E

Meets EU Safety, Health and Environmental Protection Requirements



Characteristics







HEPA - High Filtration Included Efficiency Unit

ency Unit Recov

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility included
- For general housekeeping
- Pneumatic (air-operated)
- For wet & dry recovery
- Polyethylene recovery tank
- Mounted on a Tilting Cart (TC) for easy disposal of recovered materials

Specifications

CS-15 (TC) RE SERIES	110294	110688
Model Name	CS-15 (TC) RE	CS-15 (TC) RE HEPA
Type (Powerhead)	Pneumatic	Pneumatic
Venturi	Single	Single
Venturi (diam.)	6 mm	6 mm
Minimum Compressor	15 HP	15 HP
Air Line Size (Diam.)	1/2" (12.7mm)	1/2" (12.7mm)
Input Air Volume	21.2 L/s	21.2 L/s
Input Air Pressure	5.5 Bar	5.5 Bar
Air Flow	204 m ³ /h	204 m ³ /h
Vacuum Pressure	4320 mm H ₂ 0	4320 mm H ₂ 0
Suction Inlet	38 mm	38 mm
Cart Type	Tilt Cart (TC)	Tilt Cart (TC)
Filter Cleaning	None	None
Dust Recovery Tank	47.3 L	47.3 L
Dry Recovery - Disposable Filter Bag	19 L	19 L
Liquid Recovery Capacity	47.3 L	47.3 L
Length	74 cm	74 cm
Width	64 cm	64 cm
Height	99 cm	99 cm
Weight (Vacuum Only)	30 kg.	30 kg.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Disposable Filter Bag - Included



Tools and Accessories (Toolkit 4B) - Optional



Clear Polyliner Recovery Bags - Included



PVC Crushproof Suction Hose Assembly - Included

Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077) Website: http://www.tiger-vac.eu Email: info@tiger-vac.it