

Product sheet

MolokClassic® Light 2,0m³

ORIGINAL
MOLOK®

Suitability

2,0m³ MolokClassic Light is suitable for collecting glass and metal, mixed waste etc.
Can be divided for two waste types.

Dimensions and materials

Volume	2 m ³
Height	1200 mm, Surface container
Diameter	1700 mm
Well body material	HD Polyethylene
Lid and filling lid	HD Polyethylene
Lifting bag	Polypropylene
Reinforced lifting bag	Polypropylene + PVC

Rotation molded well body is completely waterproof. Filling hole situates about 1,1 m above ground level.
Lifting bag is made of strong woven polypropylene. Safe Working Load (SWL) is indicated in the lifting bag.
There is an aluminium lifting ring on the top of the lifting bag. A quick system or four lifting loops are attached to the lifting ring. The closing mechanism is situated at the bottom of the lifting bag.
SWL of 3,0 m³ lifting bag is 1250 kg.

Accessories

- Quick system (standard)
- Inner hinge for lid (standard when divided)
- Lifting bag (standard)
- Reinforced lifting bag
- Divided lifting bag 1/2 + 1/2
- Divided reinforced lifting bag 1/2
- Support catch for the filling lid
- Locking for filling lid
- Locking for lid

Lid alternatives

- Standard lid, diameter of the filling hole max. 600mm
- Combi lid
- Drum lid
- Vertical lid
- Lid with square filling slot

Framing alternatives

- Composite board
- Recycled plastic board
- Aluminium (natural)
- Painted Aluminium (RAL tones, RAL 7024 as standard)
- Print framing

Standards

Molok®-Deep Collection System complies with the requirements of EN13071-standard.
Molok®-lifting bags are tested according to ISO 21898-standard.

