



Meets EU Safety, Health and Environmental Protection Requirements

Characteristics



Stainless
General



SD Tools &
Accessories



HEPA -
Included



High Filtration
Efficiency Unit



Dry Recovery



Dual Motor



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Includes a complete static dissipative tool kit
- Brushless motor available

Specifications

4D-55L (DT) MFS HEPA ORDLOC SERIES	112111B
Model Name	4D-55L (DT) MFS HEPA ORDLOC SERIES
Type (Powerhead)	Electric
Tension	240 V
Frequency	50 Hz
Phase	Single
Wattage	2100 W
Power	2.1 kW
Amperage	10 A
Air Flow	375 m ³ /h
Vacuum Pressure	2180 mm H ₂ O
Type of Power Outlet	Not Included
Suction Inlet	50 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	55 L
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories