

**5-gang Cambridge roller with  
hydraulic unfolding - cast diameter**

**450 mm - 530 mm**

**Category: Soil cultivation » Rollers**

**Product code:**

**9468/9469/9470/9471/9472/9473/9480/9481**




1



2



3



4



5

**STANDARD EQUIPMENT:**

- Drawbar for lower hitch Ø 50 mm
- Hydraulic folding and unfolding
- Cambridge cast Ø 530 mm
- Axle Ø 70 mm, swivel bearing sets
- Transport lock
- 2 section hydraulic (4-hoses)
- Hydraulic accumulator on main cylinder circuit ensures an even weight distribution to each sections
- 2-circuit pneumatic brake
- Tires 400/60-15.5
- Wheels chocks

**OPTIONAL EQUIPMENT:**

- Cambridge cast Ø 450 mm
- Cambridge cast Ø 500 mm

**5-gang Cambridge roller with  
hydraulic unfolding - cast diameter  
450 mm - 530 mm**

**Category: Soil cultivation » Rollers**

**Product code:**

**9468/9469/9470/9471/9472/9473/9480/9481**

- Crosskill cast Ø 510 mm
- Cam roller Ø 500 mm
- Cutter cast Ø 520 mm
- Drawbar for upper hitch Ø 40 mm
- Ball hitch
- Hitch cross shaft cat. III and IV
- Hydraulic brake
- Warning plates with LED lights

Ref.No.	Working width /m/	Number of rings /pcs/	Power demand /HP/	Weight /kg/
Cambridge Ø 450 mm				
9468	9,0	191	140-160	4530
9469	12,3	247	160-200	5520
Cambridge Ø 500 mm				
9470	9,0	181	140-160	5100
9471	12,3	237	160-200	6300
Cambridge Ø 530 mm				
9472	9,0	191	140-160	5570
9473	12,3	247	160-200	6860
Crosskill Ø 510 mm				
9480	9,0	89	140-160	4395
9481	12,3	129	160-200	5660