


Mounted disc harrow with rubber protection and mechanical working depth adjustment

Category: Soil cultivation » Compact disc harrows
Product code: 8521N/8521Na/8522N/8522Na



STANDARD EQUIPMENT:

- 3-point linkage cat. II and III
- 2 rows of notched discs Ø 560 mm , space between rows 85 cm
- Mechanical adjustment of working depth
- Side discs Ø 510 mm mounted on hinges with adjustable working depth
- Discs rubber protection Ø 40 mm
- Tubular roller Ø 500 mm
- Arms made from certificated steel with maintenance-free hubs
- Side screens with height adjustment
- Transport width less than 3.0 m for the 3.0 m harrow (for the harrow 3.5 m transport width less than 3.5 m)

OPTIONAL EQUIPMENT:

- 2 rows of notched discs Ø 610 mm, space between rows 95 cm, outermost discs Ø 560 mm, discs rubber protection Ø 50 mm, tubular roller Ø 600 mm
- Row of harrow springs mounted at the front of the roller
- Tubular roller Ø 600 mm for disc Ø 560 mm
- Packer roller Ø 500 mm
- Packer roller Ø 600 mm

Mounted disc harrow with rubber protection and mechanical working depth adjustment

Category: Soil cultivation » Compact disc harrows
Product code: 8521N/8521Na/8522N/8522Na

- V-ring roller Ø 500 mm with scrapers
- V-ring roller Ø 600 mm with scrapers
- FLEX roller Ø 500 mm
- FLEX roller Ø 550 mm
- Rubber roller Ø 500 mm
- T-ring roller Ø 500 mm
- T-ring roller Ø 600 mm
- Flat bar roller Ø 500 mm
- Flat bar roller Ø 600 mm
- Toothed flat bar roller Ø 500 mm
- Toothed flat bar roller Ø 600 mm
- FUSION roller Ø 600 mm
- Tandem roller (tubular Ø 400 mm; flat bar Ø 400 mm)
- Reinforced, welded arms with lubricated hubs (on request)
- Maintenance-free SKF hubs
- Warning plates with LED lights

Ref.No.	Working width /m/	Plate diameter /mm/	Space between the rows /mm/	Number of disc /Pcs../	Power demand /HP/	Weight /kg/
8521	3,0	560	850	24	80-100	1418
8521a	3,0	610	950	24	80-100	1648
8522	3,5	560	850	28	90-120	1876
8522a	3,5	610	950	28	90-120	2106

Working depth: 8-9cm , max.up to15cm