

Technical sheet :

# **FRAME MOUNTED HOOK**

---



## **Benefits**

- Simple and cost efficient solutions for suspended load handling.
- Very compact attachment that preserves machine stability.
- Perfect for transporting construction elements and other loads present in construction or industrial sites.

## **Technical characteristics**

- Range from 4,000kg to 6,000kg capacity.
- Directly hitched on carriage.
- Safety: homologated swivel self locking hook.

Capacities		PC 40	PC 50	PC 60
Max. outreach (mm)	I4	475	475	475
Capacity (kg)		4000	5000	6000
Weight and dimensions				
Overall height (mm)	h17	500	500	500
Width (mm)		815	815	815
Length (mm)		606	606	606
Overall weight (kg)		120	120	120
Working Parameters				
Machine Equipment		No predisposition required	No predisposition required	No predisposition required
Hydraulic system		false	false	false

Machines compatibility	PC 40	PC 50	PC 60
Reference Number	708553	708554	939050
Skid Steer Carriage reference	-	52579090	-
MHT-X 860 S2	-	-	X
MLT 420 60 H	-	X	-
MLT 625 75 H	-	X	-
MLT 845 100 H	-	X	-
MLT 845 120	-	X	-
MLT 961-145 V+ L	-	X	X
MLT-X 625 75 H	-	X	-
MLT-X 845 120	-	X	-
MLT-X 845 120 H	-	X	-
MLT-X 961-145 V+ L	-	X	X
MT 625 H	-	X	-
MT 625 HA	-	X	-
MT 733 Easy	-	X	-
MT 933 Easy	-	X	-
MT 1033 easy	-	X	-
MT 1135	X	X	-
MT 1135 H easy ST5	X	-	-
MT 1135 HA Easy ST5	X	-	-
MT 1135 easy ST5	X	-	-
MT 1335	X	X	-
MT 1335 H easy ST5	X	-	-
MT 1335 HA easy ST5	X	-	-
MT 1335 easy ST5	X	-	-
MT 1440	-	X	-
MT 1440 A	-	X	-
MT 1440 HA	-	X	-
MT 1840	-	X	-
MT 1840 A	-	X	-
MT 1840 HA	-	X	-
MT-X 625 H	-	X	-
MT-X 733	-	X	-
MT-X 1033	-	X	-
MT-X 1440	-	X	-
MT-X 1440 A	-	X	-
MT-X 1840	-	X	-
MT-X 1840 A	-	X	-
Reference Number E-RECO	921333	921335	939050
MRT 1440 Easy T4 S1 400°	X	X	-
MRT 1440 Easy T4 S2 400°	X	X	-
MRT 1640 Easy T4 S1 360°	X	X	-
MRT 1640 Easy T4 S1 400°	X	X	-
MRT 1640 Easy T4 S2 360°	X	X	-

Machines compatibility	PC 40	PC 50	PC 60
MRT 1640 Easy T4 S2 400°	X	X	-
MRT 1840 Easy T4 S1 360°	X	X	-
MRT 1840 Easy T4 S1 400°	X	X	-
MRT 1840 Easy T4 S2 360°	X	X	-
MRT 1840 Easy T4 S2 400°	X	X	-
MRT 2145 Easy T4 S1 360°	X	X	-
MRT 2145 Easy T4 S1 400°	X	X	-
MRT 2145 Easy T4 S2 360°	X	X	-
MRT 2145 Easy T4 S2 400°	X	X	-
MRT 2150 Privilege Plus	X	X	-
MRT 2470 Privilege Plus	X	X	X
MRT 2545 Easy T4 S1 360°	X	X	-
MRT 2545 Easy T4 S1 400°	X	X	-
MRT 2545 Easy T4 S2 360°	X	X	-
MRT 2545 Easy T4 S2 400°	X	X	-
MRT 2550 Privilege Plus	X	X	-
MRT 3050 Privilege Plus	X	X	-
MRT 3255 Privilege Plus	-	X	X
MRT-X 1440 Easy 400°	X	X	-
MRT-X 1640 Easy 360°	X	X	-
MRT-X 1640 Easy 400°	X	X	-
MRT-X 1840 Easy 360°	X	X	-
MRT-X 1840 Easy 400°	X	X	-
MRT-X 2145 Easy 360°	X	X	-
MRT-X 2145 Easy 400°	X	X	-
MRT-X 2150 Privilege Plus	X	X	-
MRT-X 2470 Privilege Plus	X	X	X
MRT-X 2545 Easy 360°	X	X	-
MRT-X 2545 Easy 400°	X	X	-
MRT-X 2550 Privilege Plus	X	X	-
MRT-X 3050 Privilege Plus	X	X	-
MRT-X 3255 Privilege Plus	-	X	X



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508  
RCS Nantes