

Jenbacher type 4

An efficiency milestone

Based on the proven design concepts of types 3 and 6, the modern Jenbacher* type 4 engines in the 800 to 1,500 kW power range are characterized by a high-power density and outstanding efficiency. The enhanced control and monitoring provide easy preventive maintenance, high reliability and availability.



Reference installations

J420 St Bart's Hospital in London, United Kingdom

Fuel	Engine type	Electrical output	Thermal output	Commissioning
Natural gas	1 x J420	1,480 kW	1,624 kW	2015

Since 2015, one of the oldest hospitals in the UK has obtained cooling, heat and power from a single J420 unit. The 1.4 MW cogeneration unit includes a 250 kW absorption chiller that delivers cooling water to the hospital. The J420 engine is the cornerstone of a new energy center that has provided the facility with financial savings by boosting its energy efficiency, reliability and durability.



J420 Ashford Power Peaking Plant in Kent, United Kingdom

Fuel	Engine type	Electrical output	Commissioning
Natural gas	14 x J420	21 MW	2018

The electricity generating peaking plant at Ashford Power, Kings North Industrial Estate in Kent is operating 14 containerized Jenbacher J420 engines. When not in operation, the engines of this fully-automated plant wait on standby, prepared to be called upon and ramped up in less than 2 minutes.



J420 SV.CO Strijbisverbeek Greenhouse in Maasdijk, the Netherlands

Fuel	Engine type	Electrical output	Thermal output	Commissioning
Natural gas	1 x J420	1,501 kW	1,996 kW	2018

The Strijbisverbeek Greenhouse in Maasdijk, Netherlands, is relying on a total greenhouse CHP solution consisting of a Jenbacher J420, a complete exhaust gas system incl. catalytic reactor for CO₂ and acoustical enclosure. The energy generated in this greenhouse is used to operate its grow lights. Additionally, they are using the heat of the CHP to heat up their greenhouse in colder periods and at night.



J420 Biogas Plant in Nakornrachasima, Thailand

Fuel	Engine type	Electrical output	Commissioning
Biogas	5 x J420	7,105 kW	2012

The Chok Yuen Yong facility profits from its five J420 engines that provide reliable on-site power while also reducing electrical and energy costs. The excess electricity produced is supplied to the public grid.



Technical features

Feature	Description	Advantages
Heat recovery	Flexible arrangement of heat exchanger, two stage oil plate heat exchanger on demand	- High thermal efficiency, even at high and fluctuating return temperatures
Gas dosing valve	Electronically controlled gas dosing valve with high degree of control accuracy	- Very quick response time - Rapid adjustment of air / gas ratio - Large adjustable calorific value range
Four-valve cylinder head	Enhanced swirl and channel geometry using advanced calculation and simulation methods (CFD)	- Reduced charge-exchange losses - Central spark-plug position resulting in optimal cooling and combustion conditions
Crack connecting rod	Applying a technology – tried and tested in the automotive industry – in our powerful stationary engines	- High dimensional stability and accuracy - Reduced connecting rod bearing wear - Easy to maintain

Technical data

Configuration	V 70°		
Bore (mm)	145		
Stroke (mm)	185		
Displacement / cylinder (lit)	3.06		
Speed (rpm)	1,800 / 1,200 (60 Hz)	1,500 (50 Hz)	
Mean piston speed (m/s)	7.4 (1,200 1/min) 9.3 (1,500 1/min) 11.2 (1,800 1/min)		
Scope of supply	Generator set, cogeneration system, generator set / cogeneration in container		
Applicable gas types	Natural gas, flare gas, biogas, landfill gas, sewage gas. Special gases (e.g., coal mine gas, coke gas, wood gas, pyrolysis gas)		
Engine type	J412	J416	J420
No. of cylinders	12	16	20
Total displacement (lit)	36.7	48.9	61.1
Dimensions l x w x h (mm)			
Generator set	J412	5,400 x 1,800 x 2,200	
	J416	6,200 x 1,800 x 2,200	
	J420	7,100 x 1,900 x 2,200	
Cogeneration system	J412	6,000 x 1,800 x 2,200	
	J416	6,700 x 1,800 x 2,200	
	J420	7,100 x 1,800 x 2,200	
Container	J412	12,200 x 3,000 x 2,700	
	J416	12,200 x 3,000 x 2,700	
	J420	12,200 x 3,000 x 2,700	
Weights empty (kg)			
Generator set	J412	J416	J420
Cogeneration system	11,200	13,500	17,200
Generator set	11,800	14,100	17,800
Cogeneration system	11,800	14,100	17,800

Outputs and efficiencies

NOx <	Type	1,500 1/min 50 Hz					1,800 1/min 60 Hz					1,200 1/min 60 Hz				
		Pel (kW) ¹	ηel (%) ¹	Pt (kW) ²	ηth (%) ²	ηtot (%)	Pel (kW) ¹	ηel (%) ¹	Pt (kW) ²	ηth (%) ²	ηtot (%)	Pel (kW) ¹	ηel (%) ¹	(kW) ¹	ηth (%) ²	ηtot (%)
500 mg/m ³ _N	J412	901	42.9	945	45.0	88.0	851	41.2	980	47.4	88.6	634	43.0	618	41.9	84.9
	J416	1,202	43.0	1,252	44.8	87.8	1,141	41.4	1,307	47.4	88.9	845	43.0	824	41.9	84.9
	J416	1,000	42.6	1,053	44.9	87.5										
	J420	1,497	42.9	1,563	44.8	87.7	1,429	41.5	1,633	47.4	88.9	1,056	43.0	1,029	41.9	84.9
	J420	1,497	41.4	1,802	49.8	91.2										
250 mg/m ³ _N	J412	901	41.5	996	45.9	87.4	851	40.1	1,021	48.1	88.2	634	42.1	641	42.5	84.6
	J416	1,203	41.7	1,323	45.9	87.6	1,141	40.3	1,362	48.1	88.5	845	42.0	856	42.6	84.6
	J416	1,000	41.8	1,082	45.3	87.1										
	J420	1,497	41.6	1,652	45.9	87.5	1,429	40.4	1,702	48.1	88.5	1,056	41.7	1,085	42.8	84.5
	J420	1,497	40.4	1,867	50.4	90.7										

NOx <	Type	1,500 1/min 50 Hz					1,800 1/min 60 Hz				
		Pel (kW) ¹	ηel (%) ¹	Pt (kW) ²	ηth (%) ²	ηtot (%)	Pel (kW) ¹	ηel (%) ¹	Pt (kW) ²	ηth (%) ²	ηtot (%)
500 mg/m ³ _N	J412	749	41.8	763	42.6	84.4					
	J412	901	42.3	913	42.8	85.1	851	40.2	956	45.2	85.4
	J416	999	42.0	1,009	42.4	84.4					
	J416	1,202	42.4	1,214	42.8	85.2	1,141	40.4	1,274	45.1	85.6
	J420	1,497	42.3	1,515	42.8	85.1	1,429	40.5	1,594	45.2	85.7
250 mg/m ³ _N	J412	889	41.6	917	42.9	84.6	851	39.3	989	45.7	84.9
	J416	1,190	41.8	1,224	43.0	84.8	1,141	39.5	1,319	45.7	85.2
	J420	1,484	41.7	1,530	43.0	84.7	1,429	39.6	1,648	45.7	85.2

1) Technical data according to ISO 3046
2) Total heat output with a tolerance of +/- 8 %, exhaust gas outlet temperature 120°C, for biogas gas outlet temperature 180°C
All data according to full load and subject to technical development and modification.
Further engines versions available on request.



IJB-119004-EN

Find your local support online:
www.innio.com/en/company/providers

© Copyright 2019 INNIO. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
*Indicates a trademark

