

Product sheet

MolokClassic® Plus 3,0m³

ORIGINAL
MOLOK®

Suitability

3,0 m³ MolokClassic Plus is suitable for collecting paper, metal, glass, mixed waste etc.
Can be divided for two waste types.

Dimensions and materials

Volume	3 m ³
Height	1700 mm, 500 mm of which is installed underground
Diameter	1700 mm
Well body material	HD Polyethylene
Lid and filling lid	HD Polyethylene
Lifting bag	Polypropylene
Reinforced lifting bag	Polypropylene + PVC

Rotation molded well body is completely waterproof. Filling hole situates about 1,1 m above ground level.
Lifting bag is made of strong woven polypropylene. Safe Working Load (SWL) is indicated in the lifting bag.
There is an aluminium lifting ring on the top of the lifting bag. A quick system or four lifting loops are attached to the lifting ring. The closing mechanism is situated at the bottom of the lifting bag.
SWL of 3,0 m³ lifting bag is 1250 kg.

Accessories

Quick system (standard)
Inner hinge for lid (standard when divided)
Lifting bag (standard)
Reinforced lifting bag
Divided lifting bag 1/2 + 1/2
Divided reinforced lifting bag 1/2
Support catch for the filling lid
Locking for filling lid
Locking for lid

Lid alternatives

Standard lid, diameter of the filling hole max. 600mm
Combi lid
Drum lid
Vertical lid
Lid with square filling slot

Framing alternatives

Composite board
Recycled plastic board
Aluminium (natural)
Painted Aluminium (RAL tones, RAL 7024 as standard)
Print framing

Standards

Molok®-Deep Collection System complies with the requirements of EN13071-standard.
Molok®-lifting bags are tested according to ISO 21898-standard.

