
External Dimensions (mm)



Basic Specifications

	0: 1					
Capacity	Single Interval Type	Max 3kg	Max 6kg	Max 12kg	Max 15kg / 30lb	Max 30kg
	1/3,000	e=1g	e=2g	e=2g	e=5g / 0.01lb	e=10g
	Multi Interval Type	Max 3/6 kg		Max 6 / 15 kg	Max 15/30 kg	
	1 / 3,000	e = 1/2 g		e = 2/5g	e = 5 / 10 g	
Model				RM-50		
Display		10 segments LCD for 22 digits display				
Number of Preset Keys		24				
Display Resolution		1 / 3,000				
Paper Width		48 mm				
Printing Speed		MAX 75 mm / sec.				
Power Source		AC 100 / 117 / 220 / 230 / 240 Volts (+10%, -15%) Rechargeable battery (Option, DC 12 Volts, 5Ah) *See Foot Note				
Operating Temperature		-10 °C to +40 °C				
Standard Interface		AC receptacle, Cash drawer control port (Drive voltage is 8 Volts.), RS-232C interface, RS-485 interface				
Dimension	าร	Platter size: 286 mm (W) × 223 mm (D) Overall size: 397 mm (W) × 325 mm (D) × 267.5 mm (H)				
Net Weight		5kg 6.7kg (Battery Included)				

^{*}Under normal temperature, 20°C, RM-50 can be operated with built-in Battery charged for 8 hours, for more than 72 hours without using receipt, or 2 days using 200 receipts in 10 hours per day.

SHAGHAI TERAOKA ELECTRONIC CO., LTD.

1st Floor of #2 Building, Jia Yuan Business Center, #51 Long Wu Road, Shanghai 200232, P.R. OF CHINA

TEL: +86-21-64085151

FAX: +86-21-54900008

URL: http://www.digi-scale.com

E-MAIL: steservice@digi-scale.com









RM-50

Scale Receipt Printer

Weighing and receipt printing anywhere











Searching for a New Balance

^{*}Meet or exceed OIML Class **II** or NTEP HB44 requirements. *Specifications are subject to change without prior notice.



Features of RVI-50


RM-50: designed for weighing and cash control in the open retail market. Backed by years of experience at DIGI, the RM-50 helps your operation by delivering superb value!
























Work All Day

