

Nitroxychrom


Nitrogen generator with air compressor



Model: XXX913-CS

Ultra High Purity nitrogen generator for BTEX, VOC, sulfur analyzers and others

Dedicated for Chromatotec® products line



airTOXIC synoptic showing the pressure of the N2 generator

Chromatotec® is specialized in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt). Please visit our website for more details.

N2 UHP gas

Compact

No cylinder

VOC ppt level

Remote control

Alarms

Nitroxychrom

Nitrogen generator with air compressor



Nitrogen generator:

Thanks to Nitroxychrom, there is no need for a heavy and regular replacement of gas cylinder.

Principle:

Nitrogen is produced from air.

NITROXYCHROM employs Pressure Swing Absorption (PSA) technology with a stand-by system to produce small flows of very high purity nitrogen when it is needed.

The compressed air enters to the generator via a filter that removes contaminants and bulk moisture via an integrated auto drain. When the control system assesses that more nitrogen is required, the solenoid valves opens and the pressure is allowed to build up in the column containing Carbon Molecular Sieve CMS and a residue catcher.

This sieve absorbs the oxygen and leaves the dry nitrogen free to flow into the reservoir.

A heated catalyser is needed to eliminate the hydrocarbons down to ppt concentration level.

The flow and quality of Nitroxychrom are optimized for Chromatotec® applications, for auto GC 866.

Electronic pressure measurement of N₂ displayed in Vistachrom (can be transferred by Modbus in option).

Manufacturer warranty is provided when the gas generators are associated with Chromatotec® products line

Advantages:

- Light weight construction
- Integrated Compressor: Nitroxychrom-C
- Low power requirement
- Easy Installation
- No regular maintenance required
- Over pressure security

Product technical specifications:

Flow rate:

- Flows up to 200 cc/min (300 cc/min in option for vigiE-NOSE or airTOXIC PURGE for example)

Purity:

- Ultra High Purity to 99.9995%
- Ultra high quality for carrier gas for auto GC 866 and for dilution

Communication:

- Pressure of the reservoir remotely available on Vistachrom for easy remote diagnosis

Power Supply:

- 230 VAC 50 / 60 Hz or 110 / 115 VAC 50 / 60 Hz

Electrical consumption:

- 150 W

Dimensions and weight:

- Rack 19" – 4U
- Height: 177 mm (4U)
- Width: 482 mm (rack 19")
- Depth: 660 mm
- Net weight: 10 kg

To order:

Nitrogen generator (4U) with air compressor

Options:

Vertical configuration
Wall mounted box

Model:

XXX913-CS

Under request
Under request

Chromatotec® is continuously improving its products, therefore these specifications are subject to change without notice

To contact us: info@chromatotec.com



NORTH AMERICA

CHROMATOTEC Inc.
18333 Egret Bay Blvd, Suite 270,
Houston TX 77058 - USA
Phone: +1 (281) 335 4944
Fax: +1 (281) 335 4943

EUROPE

AIRMOTEC AG SAS
15 rue d'Artiguelongue
33240 Val de Virvée - FRANCE
Phone: +33 (0) 557 940 626
Fax: +33 (0) 557 940 620

ASIA

CHROMATOTEC Trading (Beijing) Co., Ltd.
Room 1806, Building 1,
Wanda Plaza, No.93, Jianguo Avenue,
Chaoyang District,
Beijing 100022 - CHINA
Phone : +86 (0) 105 960 3283