



BioClamp® is a patented plastic union clamp, specifically designed to meet the needs of busy pharmaceutical and bioprocessing laboratories.

## FEATURES AND BENEFITS

- Lot numbers moulded in for full traceability
- Moulded from reinforced Nylon 66 USP Class VI, FDA
- Reduce distortion on polymeric fittings when subjected to heat
- Suitable for sterilisation by autoclave and gamma irradiation
- Tamper evident feature available on 1/2" to 4" BioClamp
- Lightweight and easy to manipulate
- Class 7 cleanroom manufacturing and packing
- All components and materials contain no animal derived content
- Validation guide on request

### PRODUCT SPECIFICATIONS

Part number	Pack size	Size	Max Operating Pressure		Max Cumulative Gamma Dose	Material
NG075WHT	10 PCS	1/2" - 3/4"	150 psiG	10 bar	40 kGy	Reinforced Nylon 66
NG150WHT	10 PCS	1" - 1 1/2"	150 psiG	10 bar	40 kGy	Reinforced Nylon 66
NG200WHT	10 PCS	2"	150 psiG	10 bar	40 kGy	Reinforced Nylon 66
NG250WHT	10 PCS	2 - 1/2"	150 psiG	10 bar	40 kGy	Reinforced Nylon 66
NG300WHT	10 PCS	3"	150 psiG	10 bar	40 kGy	Reinforced Nylon 66
NG400WHT	5 PCS	4"	150 psiG	10 bar	40 kGy	Reinforced Nylon 66
NG600WHT	5 PCS	6"	90 psiG	6 bar	40 kGy	Reinforced Nylon 66
NG800WHT	5 PCS	8"	90 psiG	6 bar	40 kGy	Reinforced Nylon 66

**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of these products for all intended uses. Products must be used in accordance with applicable regulatory requirements defined in datasheet.

Aseptic Group assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to these products. The data supplied is given and accepted at the buyer's risk.

**WARRANTY:** These products are warranted to be free from defects in materials and workmanship. Any products found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of these products. Aseptic Group specifically disclaims any other liability.

2017