

OB X SELA 7

Origin - Provenance - Provenienza : C.E.E.

STRUCTURE

SEAT

Anatomical support in rigid polyurethane mould (6 mm thickness).

PADDING

SEAT

Injected polyurethane foam, CFC free, 55 kg/m³ density, 30/60 mm thickness.

UPHOLSTERY

SEAT

Simil-leather/Fabric stiched and mounted to the load-bearing support.

MECHANISMS

Plate with gas pump lever, 2.5 mm thickness, painted with black epoxy powders.

SEAT HEIGHT ADJUSTMENT

Through a class 3 gas lift with 200 mm stroke, complying with DIN 4550/4551 standards



OB X SELA 7

Origin - Provenance - Provenienza : C.E.E.

BASE

5-star base in nylon (fibreglass reinforced), Ø 650 mm.

OPTIONAL


5-star base in die-cast, brushed aluminium with chromium plated effect Ø 650 mm.

FEET

Fixed polypropylene feet, Ø 70 mm.

OPTIONAL

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair, Ø 50 mm.



DIMENSIONS - INGOMBRI

A	Seat height	Min	520 mm
		Max	750 mm
C	Seat width		480 mm
D	Max total width		640 mm
E	Seat depth		310 mm
F	Total depth		640 mm

WEIGHT 6,00 Kg

VOLUME 0,08 m3

Quantity per Box N. 1

HOBBIT



OB BB SELA 7

Origin - Provenance - Provenienza : C.E.E.

STRUCTURE

SEAT

Anatomical support in rigid polyurethane mould (6 mm thickness).

PADDING

SEAT

Injected polyurethane foam, CFC free, 55 kg/m³ density, 30/60 mm thickness.

UPHOLSTERY

SEAT

Simil-leather/Fabric stiched and mounted to the load-bearing support.

MECHANISMS TILTING

Tilting mechanism lockable in all positions by means of a lever located under the left-hand side of the seat.

SEAT HEIGHT ADJUSTMENT

Through a class 3 gas lift with 200 mm stroke, complying with DIN 4550/4551 standards



OB BB SELA 7

Origin - Provenance - Provenienza : C.E.E.

BASE

5-star base in black nylon reinforced, Ø 650 mm.

OPTIONAL

5-star base in die-cast, brushed aluminium with chromium plated effect Ø 650 mm.

FEET


Fixed polypropylene feet, Ø 70 mm.

OPTIONAL

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair, Ø 50 mm.

CASTORS

Black soft castors with grey rubber for hard floor and wooden.



DIMENSIONS - INGOMBRI

A	Seat height	Min	550 mm
		Max	750 mm
C	Seat width		480 mm
D	Max total width		640 mm
E	Seat depth		310 mm
F	Total depth		640 mm

WEIGHT 6,70 Kg

VOLUME 0,08 m3

Quantity per Box N. 1

HOBBIT



OB X SELA 9

Origin - Provenance - Provenienza : C.E.E.



STRUCTURE

SEAT

Anatomical support in rigid polyurethane mould (6 mm thickness).

PADDING

SEAT

Injected polyurethane foam, CFC free, 55 kg/m³ density, 30/60 mm thickness.

UPHOLSTERY

SEAT

Simil-leather/Fabric stiched and mounted to the load-bearing support.

MECHANISMS

Plate with gas pump lever, 2.5 mm thickness, painted with black epoxy powders.

SEAT HEIGHT ADJUSTMENT

Through a class 3 gas lift with 200 mm stroke, complying with DIN 4550/4551 standards

FOOTREST

Footrest in nylon fiberglass reinforced, Ø 450 mm, manually adjustable in height by means of a knob.



OB X SELA 9

Origin - Provenance - Provenienza : C.E.E.

BASE

5-star base in nylon (fibreglass reinforced), Ø 650 mm.

OPTIONAL


5-star base in die-cast, brushed aluminium with chromium plated effect Ø 650 mm.

FEET

Fixed polypropylene feet, Ø 70 mm.

OPTIONAL

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair, Ø 50 mm.



DIMENSIONS - INGOMBRI

A	Seat height	Min	640 mm
		Max	900 mm
C	Seat width		480 mm
D	Max total width		640 mm
E	Seat depth		310 mm
F	Total depth		640 mm
P	Diameter foot-rest		450 mm



WEIGHT 6,30 Kg

VOLUME 0,08 m3

Quantity per Box N. 1

HOBBIT



OB BB SELA 9

Origin - Provenance - Provenienza : C.E.E.



STRUCTURE

SEAT

Anatomical support in rigid polyurethane mold (6 mm thickness).

PADDING

SEAT

Injected polyurethane foam, CFC free, 55 kg/m³ density, 30/60 mm thickness.

UPHOLSTERY

SEAT

Simil-leather/Fabric stiched and mounted to the load-bearing support.

MECHANISMS TILTING

Tilting mechanism lockable in all positions by means of a lever located under the left-hand side of the seat.

SEAT HEIGHT ADJUSTMENT

Through a class 3 gas lift with 260 mm stroke, complying with DIN 4550/4551 standards

FOOTREST

Footrest in nylon fiberglass reinforced, Ø 450 mm, manually adjustable in height by means of a knob.



OB BB SELA 9

Origin - Provenance - Provenienza : C.E.E.

BASE

5-star base in black nylon reinforced, Ø 650 mm.

OPTIONAL

5-star base in die-cast, brushed aluminium with chromium plated effect Ø 650 mm.

FEET


Fixed polypropylene feet, Ø 70 mm.

OPTIONAL

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair, Ø 50 mm.

CASTORS

Black soft castors with grey rubber for hard floor and wooden.



DIMENSIONS - INGOMBRI

A	Seat height	Min	640 mm
		Max	900 mm
C	Seat width		480 mm
D	Max total width		640 mm
E	Seat depth		310 mm
F	Total depth		640 mm
P	Diameter foot-rest		450 mm

WEIGHT 7,00 Kg

VOLUME 0,08 m3

Quantity per Box N. 1

HOBBIT

