




STRONG RELIABLE AND USER FRIENDLY FOR TRACTORS UP TO 280 HP





One piece all welded headstock and side bars for maximum strength when carrying a drill. Built in compartments for storage of spare blades, tools, etc.

Spring loaded 8mm side guards with replaceable wearing strips.



TECHNICAL FEATURES

8mm thick trough.

Rotor assembliey supported by high quality tapered roller bearings protected by a bottom oil seal and mechanical labyrinth system.

Sealing between parts with O Rings not with paper gaskets for highest reliability against oil leaks.

60mm rotor shafts with bolted on forged, circular blade holders for maximum strength and quick replacement of the oil seal in the event of a failure.

280 Hp Gearbox coupled to the rotor through a splined coupling with the following advantages:

Power transmitted trough the gears, not through the shaft splines

All rotor assemblies are the same

The gearbox can easily and quickly be removed from the machine for servicing Vibration from the rotor are not transmitted to the gearbox avoiding damages to the gears.

40mm thick bottom housings shaped to fill the bottom of the trough for extra stone protection.


18mm boron steel blades fitted to circular carriers for best performances in stony conditions.

Rear adjustable clod bar mounted to the roller for even and constant soil leveling when repositioning the roller.

Parallel linkage mounted rear roller to keep unaltered the angle between the clod bar and soil when readjusting the roller.

MODELLO	600			100		E865/03	T	1	Kg
	kW	HP	cm	cm	cm	cm	nr	nr	
RK 300	88-191	120-260	300	306x150x135	150 === 150	30	12	24	1785
RK 350	103-191	140-260	350	356x150x135	175 - 175	30	14	28	1905
RK 400	118-191	160-260	400	406x150x135	200 ===== 200	30	16	32	2025
RK 450	133-191	180-260	450	456x150x135	225 225	30	18	36	2145
RK 500	147-191	200-260	500	506x150x135	250 250	30	20	40	2265







Via Dell'Artigianato 11 - 47014 MELDOLA - ITALY PHONE: +390543494602 - FAX: +390543494727 Email: sales@conceptagri.com