

Swini



Description :

Surface mounted LED spotlight


Uses :

Supermarkets, shops, etc....

Product informations :

LED driver included / Material : extruded aluminium

Dimensions :



Wattage, luminous flux and performance :

		Flux	Wattage	Performance	Lamp life
3000°K	3000 Lm	3301 Lm	20,4 W	162 Lm/W	50 000 hours L80 F10
3000°K	5000 Lm	4972 Lm	32,6 W	153 Lm/W	50 000 hours L80 F10
3000°K	5400 Lm	5423 Lm	36,5 W	149 Lm/W	50 000 hours L80 F10
		Flux	Wattage	Performance	Lamp life
4000°K	3000 Lm	3430 Lm	20,4 W	168 Lm/W	50 000 hours L80 F10
4000°K	5000 Lm	5098 Lm	32,6 W	156 Lm/W	50 000 hours L80 F10
4000°K	5400 Lm	5561 Lm	36,5 W	152 Lm/W	50 000 hours L80 F10



LED Spotlight SWINI on triple circuit rail adaptor...


Mountings :

Triple circuit rail adaptor mounted

Finishes :

White (9016G) / Grey (9006G) / Black (9005G) / RAL colour chart

Light distribution curves :



(Ta < 35°C)

Not contractual document

