



Catalogue
CATERING
Chapter
REFRIGERATION

Model
 AFP-651-I


19059666

20/06/2019

PROFESSIONAL REFRIGERATION CABINET, AFP-651-I
 Stainless steel external case.
 Inner body in food-standard ABS material.
 Interior corners and edges rounded to facilitate cleaning.
 Door with handle incorporated.
 Reversible door.
 Equipped with lock and key as standard.
 Digital thermometer with temperature control.
 Supplied with 3 upper racks and 1 rack for the lower space. Valid for GN-2/1 grids.
 Guides inbuilt into the sides of the cabinet with anti-tip system.
 Drain inside the chamber.
 Forced refrigeration.
 Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
 R-600a hydrocarbon refrigerant gas.
 Operational temperature: -1 °C ÷ +6 °C.
 Ambient temperature 32 °C.
 Operational voltage: 230 V 1N - 50 Hz.
 Inner capacity: 600 litres.
 Climatic class: 4
 Energy efficiency class: D
 Electric power: 186 W.
 Dimensions: 780 x 740 x 1.865 mm

DIMENSIONS

| | | | |
|------------|----------|----------------|----------|
| X Width | 780 mm | X Gross width | 820 mm |
| Y Depth | 740 mm | Y Gross depth | 780 mm |
| Z Height | 1865 mm | Z Gross height | 2010 mm |
| Net Weight | 85,0 kg | Gross Weight | 98,0 kg |
| Net volume | 1,076 m3 | Gross volume | 1,286 m3 |



ELECTRICITY TECHNICAL SPECIFICATIONS

| | |
|--------------------|-----------|
| Electric power | 0,186 kW |
| Voltage | 230V - 1N |
| Amperage | 1.3A |
| Electric frequency | 50Hz |

GAS TECHNICAL SPECIFICATIONS

| | |
|----------|--------|
| Gas type | R-600a |
|----------|--------|

COLD TECHNICAL SPECIFICATIONS

| | |
|---------------------------|------------|
| Refrigeration power | 0,292 kW |
| Annual elec. consumption | 954,00 kWh |
| Power consumption 24h | 2,61 kWh |
| Refrigeration net.vol | 511 L |
| Climate class | 4 |
| Cooling gas load | 78,000 g |
| Clasif. Energy efficiency | D |

CONNECTIONS TECHNICAL SPECIFICATIONS

| | |
|--------------------------|---------------|
| Single-phase 230V wiring | 2X1,5+T - 6 A |
|--------------------------|---------------|



Catalogue
CATERING

Chapter
REFRIGERATION

Model
AFP-651-I

19059666

20/06/2019

