

# Passive High Voltage Probes

P5100 \* P5102 \* P6015A

## Characteristics



P5100.

[Features](#)

[> Specs](#)

[Ordering Information](#)

[Pricing Information](#)

[Request a Quote](#)

## P6015A/P5100/P5102

Probe	Nominal Length	Attenuation	Bandwidth	Risetime	Loading	Max. Input V DC or RMS	Comp. Range in pF	Readout
P6015A	10 ft.	1000X	75 MHz	4.0 ns	100 megaohm/3 pF	20 kV	7 to 49	No
P6015A Opt. 1R	10 ft.	1000X	75 MHz	4.0 ns	100 megaohm/3 pF	20 kV	7 to 49	Yes
P6015A Opt. 25	25 ft.	1000X	25 MHz	14 ns	100 megaohm/4 pF	20 kV	7 to 49	No
P6015A Opt. 2R	25 ft.	1000X	25 MHz	14 ns	100 megaohm/4 pF	20 kV	7 to 49	Yes
P5100	10 ft.	100X	250 MHz	1.75 ns	10 megaohm/2.75 pF	2.5 kV	7 to 30	Yes
P5102	2 m	10X	100 MHz	3.5 ns	5 megaohm/11.2 pF	1,000 V <sub>RMS</sub> CATII	24 to 28	No

 [Top of Page](#)




---

Tektronix Measurement products are  
manufactured in ISO registered facilities.

[Features](#)

[> Specs](#)

 P5100/5102 Only

49A-10733-4p555, 06/1997, 08/03/2000

[Ordering Information](#)

[Pricing Information](#)

[Request a Quote](#)