



Loading Forks LG with Security Chain

With automatic center-of-gravity balance for lifting and transport by crane.

Automatic-Centre-of Gravity-Balance due to a spring-loaded slide.

▷ Continuously adjustable fork distance from 395 to 965 mm with LG-15 and from 415 to 965 mm with LG-20 (outer).

▷ Nominal height is adjustable from 1100 to 1700 mm via locking pins.

▷ With security chain to prevent the load from slipping off and tipping over.

▷ Hollow Forks with conical tapered tips for optimal insert underneath the pallets.

LG-20-NH: Configuration as like as LG-20 with additional permanently installed net holder for increased safety.

Type	Fork Lengths mm (in)	Fork Dimension mm (in)	Working Load Limit WLL kg (lbs) at 500 mm (20" in)	Dead Weight kg (lbs)	Order-Number
LG-15	1,000 (40")	120 x 40 (4 ³ / ₄ x 1 ¹ / ₂ ")	1,500 (3,300)	120 (265)	5600.0059
LG-20	1,150 (45")	120 x 40 (4 ³ / ₄ x 1 ¹ / ₂ ")	2,000 (4,400)	150 (330)	5600.0060
LG-20-NH	1,150 (45")	120 x 40 (4 ³ / ₄ x 1 ¹ / ₂ ")	2,000 (4,400)	approx. 165 (360)	5600.0061
LG-15/20-NH-SSN	Net holder incl. Security net SSN for LG-15 and LG-20				4500.0044
SSN-1,3 x 1,3 x 1,85	Security net				5500.0025

For the function of the Automatic-Center-of Gravity-Balance the minimum load of 25 % of nominal load necessary