



miniSVS - Sound Velocity Sensor

Valeport's unique digital time of flight technology gives unmatched performance figures, with signal noise an order of magnitude better than any other sensor. The miniSVS is available in a selection of configurations and with optional pressure or temperature sensors. There are a number of size options to suit many applications.

The miniSVS is titanium housed as standard and 6000m rated, its rugged design allows it to withstand the toughest conditions.

DATA SHEET

Product Details



SOUND
SPEED



DIALOGUE
X2 SOFTWARE

Valeport Limited
St. Peter's Quay, Totnes,
Devon TQ9 5EW United Kingdom

Telephone: +44 (0) 1803 869292
Email: sales@valeport.co.uk
www.valeport.co.uk



Sound Velocity Measurement

Each sound velocity measurement is made using a single pulse of sound traveling over a known distance, so is independent of the inherent calculation errors present in all CTDs. Our unique digital signal processing technique virtually eliminates signal noise, and gives almost instantaneous response; the digital measurement is also entirely linear, giving predictable performance under all conditions.

Range	1375 - 1900m/s	
Resolution	0.001m	
Accuracy	Dependent on sensor size	
100mm	Random noise (point to point) Max systematic calibration error Max systematic clock error Total max theoretical error	$\pm 0.002\text{m/s}$ $\pm 0.013\text{m/s}$ $\pm 0.002\text{m/s}$ $\pm 0.017\text{m/s}$
50mm	Total max theoretical error	$\pm 0.019\text{m/s}$
25mm	Total max theoretical error	$\pm 0.020\text{m/s}$

Acoustic Frequency: 2.5MHz

Sample Rate: Selectable, dependent on configuration

Rate	SV	SV+P	SV+T
Single Sample	•	•	•
1Hz	•	•	•
2Hz	•	•	•
4Hz	•	•	•
8Hz	•	•	•
16Hz	•	•	•
32Hz	•	•	•
60Hz	•	•	•

Optional Sensors

The miniSVS may be optionally supplied with either a pressure or temperature sensor. Data is sampled at the rates shown above.

Sensor Type	Pressure	Temperature
Range	Strain Gauge 2, 5, 10, 50, 100, 300or 600 Bar	PRT -5°C - +35°C
Resolution	0.001°C range	0.001°C
Accuracy	$\pm 0.05\%$ range	$\pm 0.01^\circ\text{C}$

Data Output

The miniSVS has RS232 & RS485 output, selected by command code. RS232 data may be taken directly into a PC over cables up to 200m long, whereas RS485 is suitable for longer cables (up to 1000m) and allows for multiple addressed units on a single cable.

Baud Rate	2400 - 115200 (NB. Low baud rates may limit data rate)
Protocol	8 data bits, 1 stop bit, No parity, No flow control

Electrical

Voltage	9 - 28V DC
Power	0.25W (SV only) 0.35W (SV + Pressure)
Connector	SubConn MCBH6F (alternatives on request)

Data Format

Examples of data formats are:

```
<space>{sound_velocity}<CR><LF>
<space>{pressure}<space>{sound_velocity}<CR><LF>
<space>{temperature}<space>{sound_velocity}<CR><LF>
```

SV	Choose from: mm/s (1510123) m/s to 3 decimal places (1510.123) m/s to 2 decimal places (1510.12)	
Pressure	If fitted, pressure is always output in dBar with 5 digits, with a decimal point, including leading zeros if necessary. Position of the point is dependent on sensor range, e.g.	
	50dBar	47.123
	100dBar	047.12
	1000dBar	0047.1
Temperature	If fitted, temperature is output as a 5 digit number with 3 decimal places and leading zeros, signed if negative, e.g.	
	21.456	02.298 -03.174

Physical

Please refer to factory for detailed dimensions if required.

Depth Rating	6000m (Titanium)
Weight	1kg (housed type)
Housing & Bulkhead	Titanium
Transducer Window	Polycarbonate
Sensor Legs	Carbon Composite
Reflector Plate	Titanium

Ordering

All systems supplied with operating manual and carry case. OEM units come with a test lead, housed units with a 0.5m pigtail.

Configuration	100mm	50mm	25mm
Titanium Housing	0652004	0652005	0652006
Bulkhead OEM	0652001	0652002	0652003
Remote OEM	0652007	0652008	0652009
Titanium + Pressure	0652004-P-XX	0652005-P-XX	0652006-P-XX
Titanium + Temperature	0652004-T	0652005-T	0652006-T
Note	XX Where P = 2, 5, 10, 50, 100, 300 and 600 Bar.		

Datasheet Reference: miniSVS | April 2020

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2020

