



Catalogue
CATERING
Chapter
REFRIGERATION

Model
 AFP-451-I


19059665

20/06/2019

PROFESSIONAL REFRIGERATION CABINET, AFP-451-I
 Stainless steel external case.
 Inner body in food-standard ABS material.
 Interior corners and edges rounded to facilitate cleaning.
 Door with handle incorporated.
 Reversible door.
 Equipped with lock and key as standard.
 Digital thermometer with temperature control.
 Supplied with 3 upper racks and 1 rack for the lower space.
 Guides inbuilt into the sides of the cabinet with anti-tip system.
 Drain inside the chamber.
 Forced refrigeration.
 Evaporator integrated into the back wall of the cabinet. A fan distributes the cold, obtaining a uniform temperature inside.
 R-600a hydrocarbon refrigerant gas.
 Operational temperature: -1 °C ÷ +6 °C.
 Ambient temperature 32 °C.
 Operational voltage: 230 V 1N - 50 Hz.
 Inner capacity: 460 litres.
 Climatic class: 4
 Energy efficiency class: D
 Electric power: 186 W.
 Dimensions: 626 x 740 x 1.865 mm

DIMENSIONS

X Width	626 mm	X Gross width	666 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	74,0 kg	Gross Weight	85,0 kg
Net volume	0,864 m3	Gross volume	1,044 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,186 kW
Voltage	230V - 1N
Amperage	1.3A
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,292 kW
Annual elec. consumption	866,00 kWh
Power consumption 24h	2,37 kWh
Refrigeration net.vol	395 L
Climate class	4
Cooling gas load	81,000 g
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
--------------------------	---------------



Catalogue
CATERING

Chapter
REFRIGERATION

Model
AFP-451-I

19059665

20/06/2019

