

Technical data

Technical data, Citymaster 2000 basic vehicle	
Engine and transmission	
Engine	<ul style="list-style-type: none"> • Water-cooled, 4-cylinder Volkswagen diesel engine with 1,968 ccm • 75 kW output at 3,000 rpm, operating speed 1,600 (ECO) - 2,300 rpm • Direct fuel injection • 56 litre tank volume
Pollutant emissions/ Approval	<ul style="list-style-type: none"> • Engine emissions below the limit values compliant with EURO 5, EEV status
Drive	<ul style="list-style-type: none"> • Type approval of basic vehicle as a work machine • Hydrostatic drive, work mode, transition mode, transport mode, rear axle drive • Drive control with automatic load regulation in transport and transition mode or specifying the engine speed (work mode) • Differential lock (option)
Device drives	<ul style="list-style-type: none"> • Load-sensing high pressure hydraulics with variable power distribution • Fan speed can generally be adjusted independent of the engine speed • Additional equipment for multipurpose deployment via winter service option
Driving and work characteristics	
Speed	<ul style="list-style-type: none"> • Driving speed, automotive 0–50 km/h, standard steering • Transition mode, automotive 0–25 km/h, all-wheel steering • Work mode, hydrostatic 0–15 km/h, all-wheel steering • Reversing, 0–10 (25) km/
Chassis and steering	<ul style="list-style-type: none"> • Utility vehicle ladder-type chassis with 2 steering axles • Helical springs with shock absorbers on all axles
Brakes	<ul style="list-style-type: none"> • Multiple safety brake system with hydrostatic brake via drive • Additional hydraulic service brake via foot pedal, load-dependent brake force distribution • Mechanical parking brake
Tyres	<ul style="list-style-type: none"> • 215/70 R 15C (series production), special tyres on request
Driver's cab	<ul style="list-style-type: none"> • 2-seat comfort cab with driver's seat adjustable to the driver's weight • Ergonomic arrangement of all operating controls • 2-fold adjustable steering column • Hot water heater with air-con system as standard feature • Framed doors with sliding windows • Hinged wing mirror, adjustable from inside
Load values	
Permissible total weight	3,500/4,500/5,000 kg
Permissible axle load	2,700/2,700 kg (front/rear)
Dimensions	
H/W/L	<ul style="list-style-type: none"> • Sweeper 2-brush: 1,999 mm (cab) x 1,300 mm (standard tyres) x 3,450 mm • Sweeper 3-brush: 1,999 mm (cab) x 1,300 mm (standard tyres) x 4,860 mm
Wheelbase	1,900 mm
Gauge	1,033 mm

We reserve the right to make technical improvements to machines with regard to shape, colour and design without notice. Please ask your local Hako sales & service partner about country-specific deviations where applicable. Illustrations could contain optional equipment.