

MULTI-FUNCTION GRAPE HARVESTER



6030

NEW OXBO 6030



MULTI-FUNCTION GRAPE HARVESTER

6030

The new Oxbo 6030 multi-function grape harvester brings powerful performance, tight turning, and flexible operation to the vineyard market. With the 6030, you have the choice of removing the picking unit and using the power unit to spray or perform other vineyard tasks or using it as a dedicated harvester—whichever best fits your business needs. The operator is always positioned over the top of the vines for the best visibility and the harvester was designed to deliver the highest quality grapes.


With a powerful ground drive system, road speeds of over 20mph, and integrated technology, the 6030 was designed to deliver efficiency in the vineyard.



UNIQUE FEATURES

- Independent power unit with removable picking unit
- Designed for performance and stability in challenging ground conditions
- Tight turning radius- compatible with 18 foot headlands
- Center mounted cab for increased driver visibility
- Integrated technology and easy to use diagnostics
- P Designed and manufactured in the USA

Headland







NEW OXBO 6030

HARVESTING UNIT

High fruit retention catching system

High capacity bucket conveyance

Customizable discharge options- bin(s) and/or side discharge/over-the-row conveyor

CLEANING OPTIONS

Standard cleaning- Oxbo's three fan system has proven most effective at removing MOG

PremiumSort* cleaning- delivers the highest quality fruit, with onboard destemming and sorting

INTEGRATED TECHNOLOGY

FleetCommand- gives machine owners and managers remote access to near real-time harvester data

YieldTracker*- allows customers to produce yield maps to gain insight on yield distribution throughout the vineyard





√ POWERFUL GROUND DRIVE SYSTEM

The 6030 features a powerful ground drive system with built in traction control which was designed to handle the challenging ground conditions and steep terrain found in many vineyards. The 6030 features 26-inches of side to side leveling giving it smooth performance, even in side hills or terraced vineyards. With a maximum road speed of over 20mph, the 6030 can quickly move between blocks, minimizing the time spent in transport.



✓ CENTER MOUNTED CAB

The center mounted cab on the Oxbo 6030 gives the operator a clear view over the top of the vines. Easy to use, bi-lingual controls with built-in diagnostics and an enhanced joystick make the 6030 simple to operate.



MEASUREMENTS



	6030 (with picking unit)	
Dimensions		
Length	18ft 5in	5.61m
Width	10ft	3.05m
Tunnel width	2ft 6in	0.76m
Minimum height	12ft 6in	3.81m
Lift	26in	0.66m
Weight	24,600lbs	11,158kg
Tires		
Front tire size	440/65R24	
Rear tire size	19.5-24	
Optional rear tires	N/A	
Engine		
Engine	CAT® turbo charged, Tie	er IVF
Other Specifications		
Transmission	Danfoss H1 tandem	
Final drives	Fairfield	
Hydraulics	Danfoss 147cc pump	

Oxbo International 270 Birch Bay Lynden Road Lynden, WA 98264

Descriptions and specifications subject to change without notice.

©2020 Oxbo International Corp. A member of Ploeger Oxbo Group. 60302020.pdf



360.354.1500 888.656.7826

WWW.OXBO.COM