

One-piece Campbell roller mounted at the front

Category: Soil cultivation » Rollers

Product code:

9015/9016/9019/9020/9023/9024/9250/9325/9326/9327/9328



1



2



3



4

STANDARD EQUIPMENT:

- 3-point linkage cat. II or III
- Supporting leg
- Double spring stabilization system
- Swivel bearing sets
- Cleaning chains
- Campbell cast Ø 700 mm, blade angle 30°, weight 31 kg, axle Ø 55 mm

OPTIONAL EQUIPMENT:

- Campbell cast Ø 700 mm, blade angle 45°, weight 42 kg, axle Ø 55 mm
- Campbell cast Ø 800 mm, blade angle 30°, weight 48 kg, axle Ø 55 mm
- Campbell cast Ø 900 mm, blade angle 36°, weight 67 kg, axle Ø 60 mm
- Two-row cultivator
- Three-row cultivator
- Spring leveling board with hydraulic working depth and angle adjustment
- Warning plates with LED lights

Attention: working width ~ transport width.

One-piece Campbell roller mounted at the front

Category: Soil cultivation » Rollers

Product code:

9015/9016/9019/9020/9023/9024/9250/9325/9326/9327/9328

Ref.No.	Working width /m/	Number of rings /pcs/	Power demand /HP/	Weight /kg/
Campbell ø 700 mm, 30°, 31 kg				
9015	3,0	20	60-70	940
9016	3,4	22	70-80	1020
9325	4,0	26	80-90	1170
9505	4,0 (hydraulic folding)	25	110-130	1510
9510	6,0 (hydraulic folding)	39	160-190	1860
Campbell ø 700 mm, 45°, 42 kg				
9019	3,0	19	60-70	1100
9020	3,4	22	70-80	1240
9326	4,0	26	80-90	1430
Campbell ø 800 mm, 30°, 48 kg				
9250	3,0	19	60-70	1260
9251	3,4	22	70-80	1420
9327	4,0	26	80-90	1640
Campbell ø 800 mm, 36°, 71 kg				
9023	3,0	15	60-70	1790
9024	3,4	18	70-80	1950
9328	4,0	21	80-90	2300

cultivator (attachment)

Ref.No.	Working width /m/	Number of rows /pcs/	Power demand /HP/
9403	3,0	2	20
9404	3,4	2	20
9407	3,0	3	30
9408	3,4	3	30