



HC30 SPECIFICATIONS

BATTERY DESIGN

- Absorbent glass mat (AGM) technology 12V battery VRLA
- Can be mounted in any orientation except inverted.
- US DOT and IATA certified non-spillable
- Can be fitted with TP brass automotive adaptor on request.
- Sealed Construction (Non-Spillable Battery)
- Shipped fully charged - just install and go!
- Suited for repeated discharges such as running your vehicle with winches or other electrical accessories.

PERFORMANCE FEATURES

- ✧ PHCA: 950A at 80°F (27°C) for 5 seconds
- ✧ CCA: 450A at 0°F (-18°C)
- ✧ CA/MCA: 550A at 32°F (0°C)
- ✧ HCA: 635A at 80°F (27°C)
- ✧ Reserve capacity: 60minutes
- ✧ Short circuit current: 1550A
- ✧ Operation temperature range: -5°F (-15°C) to 122°F (50°C)

Nominal Dimensions

Length		Width		Height		Total Height		Weight	
mm	in	mm	in	mm	in	mm	in	kg	pound
250	9.84	97	3.82	142	5.59	156	6.14	10.60	23.37

HIGH RATE DISCHARGE AT 77°F (25°C)

5 sec.	10 sec.	20 sec.	30 sec.
950A	850A	720A	635A

EXTENDED DISCHARGE AT 77°F (25°C) TO 10.02V

5min	15min	1hr	3hr	5hr	10hr	20hr
134A	60.8A	20.2A	7.89A	5.0A	2.72A	1.50A

PHYSICAL CHARACTERISTICS

