

Fiche technique :


80 VJR




Capacities		Métrique	Impérial
Working height	h21	7.65 m	25 ft 1 in
Platform height*	h7	5.65 m	18 ft 6 in
Max. outreach	l4	3.24 m	10 ft 8 in
Overhang	l5	4.235 m	13 ft 11 in
Pendular arm rotation (bottom)		-70 °	-70 °
Platform capacity	Q	200 kg	441 lbs
Turret rotation		350 °	350 °
Number of people (inside / outside)		2 / 1	2 / 1
Weight and dimensions			
Platform weight*		2250 kg	4960 lbs
Platform dimensions (length x width)	lp / ep	1.11 m x 0.93 m	3 ft 8 in x 3 ft 1 in
Overall width	b1	0.99 m	3 ft 3 in
Overall length	l1	2.95 m	9 ft 8 in
Overall height	h17	1.99 m	6 ft 6 in
Floor height (access)	h20	0.47 m	1 ft 7 in
Jib length	l13	1.5 m	4 ft 11 in
Counterweight offset (turret at 90°)	a7	0.09 m	4 in
Internal turning radius (over tyres)	b13	0.59 m	1 ft 11 in
Outer turning radius	Wa3	2.09 m	6 ft 10 in
Plugs / stability bars ground clearance	m6	0.02 m	1 in
Ground clearance at centre of wheelbase	m2	0.09 m	4 in
Wheelbase	y	1.2 m	3 ft 11 in
Performances			
Drive speed - stowed		4.5 km/h	2.8 mph
Drive speed - raised		0.7 km/h	0.4 mph
Gradeability		25 %	25 %
Permissible leveling		2 °	2 °
Wheels			
Tyres type		Solid non-marking tires	Solid non-marking tires
Dimensions of front wheels		0,41x0,13m	0,41x0,13m
Drive wheels (front / rear)		0 / 2	0 / 2
Steering wheels (front / rear)		2 / 0	2 / 0
Braking wheels (front / rear)		0 / 2	0 / 2
Engine			
Electric engine power rating		1.5 kW	1.5 kW
Electric Pump		3 kW	3 kW
Number of hydraulic pump / Capacity of hydraulic pump		2 x 4.2 cm ³	2 x 0.26 in ³
Power (kW)		3 kW	3 kW
Battery / Batteries capacity		24 V / 250 A	24 V / 250 A
Integrated charger (V / Ah)		24 V / 30 A	24 V / 30 A
Miscellaneous			
Number of cycles with STD Battery (HIRD)		32	32
Ground Pressure		11.1 daN/cm ²	11.1 daN/cm ²
Hydraulic Pressure		140 Bar	10 PSI
Hydraulic tank capacity		22 l	4.84 gal
Vibration on hands/arms		2.5 Nm	8.2 ft/s
Standards compliance			
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)	European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)

*Varies according to options and standards of the country to which the machine is delivered

Abaques



Schémas d'encombrement



Équipements

Standard

- Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
- Battery charge indicator lamp
- CAN bus technology
- Emergency stop button in platform and on frame
- Fixed pothole protection
- Fork pockets
- Hour meter
- Integrated charger
- Integrated diagnostic assistance
- Manual emergency lowering
- Negative-type braking on rear wheels
- Non-marking rubber tyres
- Pendular arm
- Proportional controls
- Slings and securing rings
- Tool box in platform
- Traction battery
- lace floor basket

Optionnel

- 230V Predisposition
- Air predisposition
- Beep on every movement
- Centralized recharging of battery
- Extreme cold oil
- Flashing Light
- Maintenance-free battery
- Personalized paintwork
- SMS : Safe Man System
- Safety harness
- Working light



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



Cette publication présente le descriptif des versions et possibilités de configuration des produits Manitou qui peuvent différer en équipement. Les équipements présentés dans cette brochure peuvent être de série, en option, ou non disponibles suivant les versions. Manitou se réserve le droit, à tout moment et sans préavis, de modifier les spécifications décrites et représentées. Les spécifications portées n'engagent pas le constructeur. Pour plus de détails, contactez votre concessionnaire Manitou. Document non contractuel. Présentation des produits non contractuelle. List des spécifications non exhaustive. Les logos ainsi que l'identité visuelle de l'entreprise sont la propriété de Manitou et ne peuvent être utilisés sans autorisation. Tous droits réservés. Les photos et schémas contenus dans la présente brochure ne sont fournis qu'à des fins de consultation et à titre indicatif.

MANITOU BF SA - Société anonyme à conseil d'administration - Capital social : 39 547 824 euros - 857 802 508 RCS Nantes