



1



2



3



4



5

**STANDARD EQUIPMENT:**

- Hitch cross shaft cat. III and IV
- Cambridge cast  $\varnothing$  530 mm (4 spoke)
- Central axle  $\varnothing$  70 mm swivel bearing sets
- Hydraulic folding and unfolding
- Hydraulic flow divider allows evenly unfolding side sections
- Hydraulic accumulator on main cylinder circuit ensures an even weight distribution to each sections
- ISOBAR hydraulic system which ensures evenly pressure distribution on sides and ground contour following
- Mechanical transport lock
- Transport width less than 3 m
- 3 section hydraulic (6-hoses) + 1 section (1-hose for brake)

**5-gang Cambridge roller with hydraulic unfolding - ISOBAR system- casts diameter 530-600 mm**

Category: Soil cultivation » Rollers

Product code: 9475/9475A

- Hydraulic brake
- Tires 400/60-15.5
- Wheels chocks

**OPTIONAL EQUIPMENT:**

- Cambridge cast Ø 600 mm
- Cutter cast Ø 520 mm
- Ø 610 mm pipe for water filling - smooth roller
- Lower drawbar pivoting hitch Ø 50 mm
- Upper drawbar hitch Ø 40 mm
- Ball hitch
- 2-circuit pneumatic brake
- Wheels 520/50 - 17
- Mudguards
- Stone boxes (2 pcs)
- Warning plates with LED lights

Ref. No.	Working width /m/	Number of rings /pcs./	Power demand /HP/	Weight /kg/
Cambridge Ø 530 mm				
9475	12,3	247	160-190	6860
Cambridge Ø 600 mm				
9475A	12,3	239	160-190	8000