

### RP-X617

1920 x 1200  
WUXGA



### Display Features & Benefits

- ▶ 6U rackmount 17" widescreen LCD
- ▶ 1920 x 1200 native **WUXGA** Ultra high resolution
- ▶ PIP & Picture by Picture viewing efficiency
- ▶ Green LED-backlit panel technology
- ▶ 8-bit colors
- ▶ Built-in HDMI, DVI-D, VGA, S-Video + BNC & Audio

### Options

- 3G / HD / SD-SDI Broadcast-grade input
- **MCS** Multi-display control solution
- X17" Touchscreen : Capacitive, Resistive
- DC power : 12V / 24V / 48V / 110 ~ 125V
- MIL-type or lockable connector



**Basic I/O :** VGA + DVI-D + HDMI + BNC + S-Video + audio  
**Options :** SDI, USB for touchscreen & DC power

### Specifications

#### • LCD Panel

Size (diagonal) :	17.1" widescreen TFT
Max resolution :	1920 x 1200
Brightness (cd/m2) :	210
Backlight :	LED
Colors :	16.7 M, 8-bit
Contrast ratio (typ) :	600 : 1
Viewing angle (H/V) :	130° x 110°
Active area (mm) :	367 x 230
MTBF (hrs) :	20,000
Signal input :	HDMI / DVI-D / VGA / S-Video / BNC

#### • Weight

Net :	4.2 kgs ( 9.2 lbs )
Gross :	6.2 kgs ( 13.6 lbs )

#### • Environmental

Operating :	0 to 50°C Degree
Storage :	-5 to 60°C Degree
Relative humidity :	5~90%, non-condensing
Shock :	10G acceleration ( 11 ms duration )
Vibration :	5~500Hz 1G RMS random vibration

#### • Casing Color :

Black ( RAL 9005 )

#### • Regulatory

Safety :	FCC & CE certified
Environmental	RoHS2 & REACH compliant

#### • Power

Input :	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption :	Max. 48 Watt, Standby 5 Watt

#### • Dimensions

Product :	480 x 48 x 266 mm / 18.9 x 1.9 x 10.5 inch
Packing :	529 x 124 x 451 mm / 20.8 x 4.9 x 17.8 inch

### Diagrams ( mm )

