




Montage à ressort anti-rotation


- Permet de compenser les différences de niveau
- Permet de conserver l'orientation des pièces
- Matière: Laiton nickelé

Raccordement fileté



Référence	G1	G	C	A	B	D	E	F	H
9FT10153130518A	M5	1/8	15	76	23	6	M12x100	38.5	2
9FT10253130518A	M5	1/8	25	86	23	6	M12x100	48.5	2
9FT20253131818A	1/8	1/8	25	113	42	14	M18X100	50	5
9FT20253131814A	1/8	1/4	25	112	42	8	M18X100	49.5	5
9FT20403131818A	1/8	1/8	40	127	42	14	M18X100	73	5
9FT20403131814A	1/8	1/8	40	127	42	8	M18X100	72.5	5
9FT30403131438A	1/4	3/8	40	158	50	14	M28X150	83	6
9FT30403131414A	1/4	1/4	40	158	50	14	M28X150	83	6
9FT30603131438A	1/4	3/8	60	178	50	14	M28X150	103	6
9FT30603131438	1/4	3/8	60	178	50	14	M28X150	103	6
9FT20603131818A	1/8	1/8	60	147	42	14	M18X100	93	5
9FT20603131814A	1/8	1/4	60	147	42	8	M18X100	84	5

Avec raccord rapide



Référence	G1	G	C	A	B	D	E	F	H
9FT10153150418A	Ø4	1/8	15	91	23	6	M12x100	38.5	2
9FT10253150418A	Ø4	1/8	25	101	23	6	M12x100	48.5	2
9FT20253150814A	Ø8	1/4	25	132	42	14	M18X100	50	5
9FT20403150814A	Ø8	1/4	40	147	42	14	M18X100	73	5
9FT20253150818A	Ø8	1/8	40	132	42	10	M18X100	49.5	5
9FT30403150814A	Ø8	1/4	40	174	50	14	M28X150	83	6
9FT20603150814A	Ø8	1/4	60	168	42	14	M18X100	93	5
9FT20603150818A	Ø8	1/8	60	168	42	10	M18X100	84	5