



ENTREE / INLET	BRIDE / FLANGE - DN25 - PN40
SORTIE / OUTLET	BRIDE / FLANGE - DN32 - PN16
MASSE / WEIGHT	7,06kg
SECTION DE PASSAGE / CROSS SECTION	S=254mm <sup>2</sup>
DIAMETRE DE PASSAGE / ORIFICE	Ø18mm
DIMENSIONS	mm
ECHELLE / SCALE	7 : 10 - A3

Rep./Item	Qté/Qty	Désignation/Description	Matière/Material
68	1	JOINT / GASKET	PTFE
63	1	JOINT DE BOUCHON / CAP GASKET	PTFE
62	1	VIS DE BOUCHON / SCREW	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
54	1	JOINT RACCORD DE SORTIE / GASKET	PTFE
52	1	BRIDE TOURNANTE / LOOSE FLANGE	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
51	1	RACCORD SORTIE / COUPLING	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
50	1	BRIDE TOURNANTE / LOOSE FLANGE	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
35	1	DOUILLE / SOCKET	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
33	1	ECROU / NUT	INOX A2 - 70
32	1	LEVIER / LEVER	1.4301 (304)
31	2	JOINT TORIQUE / O-RING	FPM
30	1	RONDELLE / WASHER	1.4307 / X2CrNi18-9 (AISI 304L)
29	1	AXE / PIN	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
27	1	BOUCHON / CAP	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
26	1	JOINT DE BOUCHON / CAP GASKET	PTFE
25	1	ECROU / NUT	INOX A2 - 70
24	1	COUELLE DE TIGE / TAPPING PLATE	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
23	1	CONTRE-ECROU VIS DE REGLAGE / LOCK NUT	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
22	1	VIS DE REGLAGE / ADJUSTMENT SCREW	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
18	1	COUELLE SUPERIEURE / UPPER SPRING PLATE	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
17	1	RESSORT (SPECIFIQUE) / SPRING (SPECIFIC)	1.4310 / X10CrNi18-8 (AISI 302)
16	1	COUELLE INFERIEURE / UNDER SPRING PLATE	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
14	1	GUIDE TIGE / STEM GUIDE	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
12	1	TIGE / STEM	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
11	1	BILLE / BALL	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
10	1	VIS / SCREW	INOX A2 - 70
09	1	DEFLECTEUR / DISC-HOLDER	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
08	1	CLAPET / DISC	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
04	1	RACCORD SIEGE / SEAT	1.4404 / X2CrNiMo17-12-2 (AISI 316L)
03	1	JOINT DE SIEGE / SEAT GASKET	PTFE
01	1	CORPS / BODY	1.4408 / GX5CrNiMo19-11-2 (CF8M)