FAAC

VALIDATION SOLUTION
Offline Voucher Printer

VPrint XT is an innovative, offline voucher printer that offers multiple ways of printing a single validation/discount to a ticket: continuous mode, either with fan fold tickets, paper roll, or single mode. Its high flexibility allows the ability to not only to customize the ticket with a distinctive layout, but also to associate a specific kind of validation/voucher to each of its 4 buttons. Among its smart features, VPrint XT allows users to set up a Wi-fi hotspot, and accessibility to any wireless device such as smartphone, PC, and tablet. VPrint XT extended functionalities can be controlled and configured via an intuitive web dashboard: from mass print and counter check to ticket layout update, the printer can be easily and comprehensively managed.

Parking Technology **HUB**

Base Model

- Desktop validation/discount voucher printer
- Multiple thermal printing modalities:
- Paper roll: recommended width 60 mm, weight 60 g/m2 to 110 g/m2
- Fan fold tickets: recommended dimensions 85.5 mm x 54 mm, weight 60 g/m2 to 150 g/m2
- 4 buttons allowing up to 4 validations/discounts set up
- 24 vdc power supply

Options

- Desktop vertical support, ideal for the retail environment

Standard Features

- Programmable via dedicated mobile app
- Intuitive web interface designed for the device set up, configuration and troubleshooting
- Easy customization of the ticket layout
- Easy-to-use online dashboard to manage the ticket mass printing, validation monitoring and counter check, set up of the customized ticket layout
- Printing in continuous mode or single ticket mode
- Dedicated Wi-fi hotspot, accessible by any wireless device eg. smartphone, PC, tablet
- Unique number for each voucher

*

Peripheral Dimensions (W x D x H)
127mm x 227mm x 105mm
With Desktop Support:
127mm x 248mm x 178mm
Weight
2,6 kg
Electrical
24 vdc 10%±
90 watt
Temperature
From -20°C to +70°C

FAAC

Parking Technology HUB

* Photo is overall representation. Peripheral components may vary based on final configuration.