

CHYPRE MONOPIÈCE

Hauteur de 6 à 9 mètres

Single piece - 6 to 9 meters height













Luminaire PHILIPS

Candélabre rond-conique mono pièce en acier, diamètre 60 ou 62 mm angle 15°.


Round-conical steel shaft, in one piece, diameter 60 or 62 mm angle 15°.



Dimensions


	 HS m	 S m	 Øa mm	 Øb mm	 Lp mm	 Pp mm	 Hp mm	 cxd mm	 E mm	 TS mm
CHYPRE 60										
7	2	60	168	500	91	500	90x116	300	J 20/18x400	
8	2	60	181	500	100	500	100x125	300	J 20/18x400	
9	2	60	199	500	102	500	100x150	300	J 20/18x400	
	2.3	60	199	500	102	500	100x150	300	J 20/18x400	
CHYPRE 62										
6	1.5	62	160	500	99	500	95x95	300	J 20/18x400	
7	1.5	62	173	500	101	500	95x110	300	J 20/18x400	
8	1.5	62	185	600	128	500	110x110	300	J 20/18x400	
9	1.5	62	200	600	132	500	115x135	300	J 20/18x400	

Accessoires et options
PORTE



Accessoires et options
PIED DE MÂT





Crosse cintrée (15°) | Curved shape (15°)

Capacités

HS m	S m	Kg	22 m/s		24 m/s		26 m/s		28 m/s		34 m/s		M m.daN	T daN	Lm x Hm m
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
CHYPRE 60															
7	2	20	0,31	0,23	0,23	0,16	0,17	0,12	0,13	0,09	0,05	-	536	117	0.6x0.6
8	2	20	0,31	0,23	0,23	0,17	0,17	0,12	0,13	0,09	0,05	-	680	131	0.6x0.6
9	2	20	0,35	0,29	0,29	0,21	0,22	0,16	0,17	0,12	0,07	-	892	153	0.6x0.7
	2,3	20	0,34	0,25	0,25	0,18	0,19	0,13	0,14	0,10	0,06	-	844	149	0.6x0.7
CHYPRE 62															
6	1,5	20	0,35	0,35	0,35	0,35	0,35	0,35	0,35	0,34	0,26	0,20	652	139	0.6x0.6
7	1,5	20	0,35	0,35	0,35	0,35	0,35	0,35	0,35	0,35	0,31	0,25	914	166	0.6x0.8
8	1,5	20	0,35	0,35	0,35	0,35	0,35	0,32	0,34	0,26	0,20	0,16	923	158	0.6x0.8
9	1,5	20	0,35	0,35	0,35	0,35	0,35	0,35	0,35	0,34	0,26	0,20	1253	189	0.6x0.9