



Meets EU Safety, Health and Environmental Protection Requirements



Chip and Coolant Recovery



### Characteristics

- Designed for the recovery of metal chips and shavings mixed with oil. Can be used for both aqueous and synthetic based coolants
- The HOGOIL's compact size allows it to be quickly moved near and around machinery to facilitate machinery maintenance and to minimize down time
- Single phase, dual motors - 2-stage heavy duty bypass type
- Equipped with 2 independent switches (one switch for each motor). There is also an indicator light for when the maximum liquid recovery capacity has been reached
- The electronic float valve automatically stops the vacuum when the container is full
- There are two filters installed upstream from the motor - a foam filter and a Dralon pre-filter
- The 2" (50 mm) suction inlet is positioned below the filters allowing for the recovery of both liquids and solids at the same time
- Metal chips and shavings are collected in the removable sieve basket. The chips/shavings are separated from the oil as they pass through the sieve basket
- A 1.25" drain valve is installed on the container for easy emptying of recovered liquids
- Oil resistant suction hose and a variety of optional accessories are available

## Specifications

HOGOIL STANDARD (EU)	112650B
Model Name	HOGOIL STANDARD
Type (Powerhead)	Electric
Tension	230 V
Wattage	2200 W
Air Flow	360 m <sup>3</sup> /h
Vacuum Pressure	2400 mm H <sub>2</sub> O
Sound Level	75 dB(A)
Suction Inlet	50 mm
Cart Type	2+2 Wheels
Filter Surface Area	12 000 cm <sup>2</sup>
Dust Recovery Tank	30 L
Liquid Recovery Capacity	90 L
Length	66 cm
Width	57 cm
Height	124 cm
Weight (Vacuum Only)	49 kg.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



Internal view model HOGOIL Standard



Foam Filter and Dralon Pre-Filter - Included



Strainer Basket for the separation and collection of metal chips and metal shavings - Included



HOGOIL PUMP and STANDARD Tool Basket



Typical application - HOGOIL in use



HOGOIL Typical application



Sieve basket after use



2" (50 mm) Oil Resistant Suction Hose & Accessories - Optional