



With balancer  
function

**Intuitive control.  
Precise positioning.**

**DCBS chain hoist**

**DEMAG** .....



## Variable speeds. Exact positioning.

### HIGHER AVAILABILITY FOR IMPROVED EFFICIENCY

Intuitive load handling has never been so easy and, at the same time, efficient: based on our DC range, DCBS chain hoists include a balancer function that allows loads to be guided and precisely positioned with ease. DCBS units are available in two sizes with load capacities up to 160 kg. They are compatible with our comprehensive Demag KBK light crane system. DCBS units can be easily installed and travel on KBK profile section rails: on single-girder suspension cranes, suspension monorail systems or on slewing jib cranes.

### HIGH SAFETY AND RELIABILITY. DCBS CORE FUNCTIONS:

- Lifting and lowering by manual force on the control handle
- Manipulating loads
- Protection against slack chain
- Protection against snatching loads
- Movements can be stopped if loads fluctuate widely
- Monitoring/reducing load capacity

### HIGH SAFETY AND RELIABILITY

- Low-wear brake thanks to regenerative braking
- No need to adjust the brake
- Brake arranged before slipping clutch in the drive arrangement (no load slipping)
- Automatic braking if a malfunction occurs
- Slipping clutch with automatic cut-out by means of speed monitoring (no continuous slipping)
- Gearbox, slipping clutch and brake maintenance-free for up to 10 years
- Safety-related functions satisfy at least Performance Level c and Category 2 to EN ISO 13849-1

### FEATURES

- Operating limit switches (upper/lower)
- Elapsed operating time counter
- Installation transparency thanks to operating data interface (IDAPSY)

### SIMPLE INSTALLATION

- Plug-in electric connections: "Plug & Lift"

# Demag chain hoist with balancer function

## Your benefits

### GRIP CONTROL

- The load can be controlled very easily with the D-Grip Servo control handle.

### LOAD POSITIONING

- By switching over to "load positioning mode", the operator can grasp and guide the load directly with light pressure.

### ASSEMBLY MODE

- High level of safety and precision for assembly operations, since any oscillation and uncontrolled load movements are suppressed.

### LOAD PICK-UP MODE

- Load handling attachments can be lifted and pre-tensioned
- Load can be removed without dropping or sudden upward pull
- Protection for jigs and machinery. The balancer only lifts until a preset force is reached.







## Technical data

		DCBS-Pro 1-125	DCBS-Pro 2-160
Model code		DCBS-Pro 1-125 H2,8 VS30 380-480/50/60	DCBS-Pro 2-160 H2,8 VS16 380-480/50/60
Load capacity	[kg]	125	160
Lifting speeds VS <sub>min</sub> /VS <sub>rated</sub>	[m/min]	0.15 - 30	0.15 - 16
Lifting height (standard)	[mm]	2,800	2,800
Increased suspension height (extra price)	[mm]	4,300	4,300
Chain size	[mm]		4.2 x 12.2
Group of mechanisms	FEM / ISO		4m / M7
Supply voltage	[V AC]		380 - 480
Frequency	[Hz]		50/60
Control voltage	[V DC]		24
Output	[kW]		0.94
Hoist motor duty factor	[%]		15 % [VS <sub>min</sub> ] / 60 % [VS <sub>rated</sub> ]
C dimension with long suspension bracket	[mm]		815.5
Equipment length	[mm]		502
Weight for hook path (2,800 / 4,300 mm)	[kg]		25 / 27
Temperature range	[°C]		- 20 to + 40 (without reduction in CDF) 50 (30 % CDF)
Protection class / insulation class			IP55 / F

### DEMAG CRANES & COMPONENTS GMBH

Wetter Site  
 Ruhrstrasse 28  
 58300 Wetter, Germany  
**E** info@demagcranes.com  
**T** +49 2335 92-0  
**F** +49 2335 92-7676  
[www.demagcranes.com](http://www.demagcranes.com)

# DEMAG