

Moniteur industriel



Moniteur étanche
Ecran capacitif PCAP / Résistif (Option)



LCD Size: 12.1" / 15" / 17" / 19" / 21.5" / 23.8" (Optional)



I/O	Video	1 x Waterproof Connector For H-DMI / VGA (Optional)
	USB	1 x SP13 Waterproof Connector For Touch USB2.0
	Other I/O Interface	1 x Power Switch
Power	Power Adapter	1 x Optional AC/DC 12V/5A , 60W
	Power Input	1 x SP13 Waterproof Connector For 12V~24V DC
	Power Consumption	≤ 30W
Touch screen	Touch Type	Optical bonding PCAP Touch
	Surface Hardness	≥7H
Environment	Operating Temperature	-20~70°C (-4~158°F)
	Storage Temperature	-30~80°C (-22~176°F)
	Relative Humidity	5%~95%@40°C, non-condensing
	Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
	IP Level	IP66 / IP69K
	EMC	CE, FCC , Class A, ROHS

Moniteur industriel



Moniteur en acier inoxydable
Ecran capacitif PCAP / Résistif (Option)



LCD Size: 12.1" / 13.3" / 15.6" / 21.5" (Optional)



I/O	Video	1 x Waterproof Connector For H-DMI / VGA (Optional)
	USB	1 x M12 Waterproof Connector For Touch USB2.0
	Other I/O Interface	1 x Power Switch
Power	Power Adapter	1 x Optional AC/DC 12V/5A , 60W
	Power Input	1 x M12 Waterproof Connector For 12V~24V DC
	Power Consumption	≤ 30W
Touch screen	Touch Type	Optical bonding PCAP Touch
	Surface Hardness	≥7H
Environment	Operating Temperature	-20~70°C (-4~158°F)
	Storage Temperature	-30~80°C (-22~176°F)
	Relative Humidity	5%~95%@40°C, non-condensing
	Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
	IP Level	IP66 / IP69K
	EMC	CE, FCC , Class A, ROHS