

Crushing, Milling & Stabilization

PTH Multi Crusher

The PTH Multi Crusher is unique in the segment of mobile stabilizing crushers. Breaking, milling and stabilization are done in just one operation !

With a maximum working depth of 500 mm, the machine crushes the hardest stones such as granite, gneis and basalt. For professionals who expect MORE !



330 - 500 HP
1.800 - 2.300 mm



Standard features		Technical details		1800	2000	2200
Complete rotor armouring for extreme operations 2 hydraulically adjustable crushing stages, interchangeable Crushing chamber armoured with replaceable HARDOX plates Carbide-tipped special tools Extra-large rushing and mixing chamber for more evenly results Overlapping tool arrangement Less wear on the tool holders 3-Point linage KAT 4 Drive shaft	Number of tools - pcs.	29+41	41+24	41+24		
	Power requirement	min. 330 - 500 HP				
	PTO Drive rpm	540 750 1.000				
	Drive double sided	high-performance drive belts				
	Dead weight approx.	8.000 kg	9.000 kg	10.000 kg		
	Working width	1.800 mm	2.100 mm	2.300 mm		
	Overall width	2.400 mm	2.700 mm	2.900 mm		
	Working depth	max. 500 mm				
	Crushing stage	hydr. adjustable 10 - 200 mm				
Special equipment						

- Trailing axle and drawbar + folding function (1800)
 - Water injection system incl. pump and electronic volume regulation via ISOBUS
- Special paint according to RAL specification
 - Water injection system excl. pump with spray boom
- articulated drawbar

