

Verge cutter for tractors, excavators & co

PTH Verge Cutter

All functions of the PTH verge cutter can be controlled hydraulically from the carriers vehicle and are characterized by their robustness based on the technology of a stone crusher.

The ideal machine for road maintenance companies, landscape construction companies, but also farmers and municipalities. It is foldable for transport.

PTH
products
MASCHINENBAU



min. 100 l/min
200 - 360 bar



Standard features

- + Carbide-tipped special tools
- + Inner armouring made of HARDOX steel changeable
- + Rotor with overlapping tool arrangement
- + low wear on the tool holders
- + Mounting fram for tractors, wheel loaders and other carriers
- + Hydraulic adjustment of cutting angle, ejection angle/range
- + Hydraulic adjustment of support wheel
- + Hydraulic adjustment from transport position into operation position

Technical details

	900	1150	1400
Number of tools - pcs.	32	40	48
Required output min.	100 l/min.	100 l/min.	120 l/min.
Pressure	200-360 bar	200-360 bar	200-360 bar
Drive	one side with 6 high-performance V-belts		
Dead weight approx.	950 kg	1.000 kg	1.050 kg
Working width	bis 900 mm	bis 1.150 mm	bis 1.400 mm
Overall width operation position	2.700 mm		
Overall width transport position	1.550 mm		
Working depth	max. 150 mm		

Specials for tractor, wheel loader, mini loaders

- Special painting according to RAL specification
- Tandem support wheel hydraulically height-adjustable
- Control block incl. Joystick and PTH tronic

Specials for excavator, crane body, mowing arm

- Adapter plate for carrier vehicle (available in different sizes)
- Combi quick change mounting

