

**Construction****Inner conductor** ① - ④

Material	Annealed Copper
Diameter	1 × Ø 0.50 ± 0.025 mm
Area	0.20 mm <sup>2</sup>

**Insulation**

Material	PVC
Diameter	Ø 1.00 mm

**Assembly**

4 Conductors	
Colors	See color table

**Mylar spiral** ⑤

Coverage	90 %
----------	------

**Drain wire** ⑥

Material	Annealed Copper
Diameter	1 × Ø 0.50 ± 0.025 mm
Area	0.20 mm <sup>2</sup>

**Screen** ⑦

Material	Alu/Polyester Tape
Coverage	≥ 115 %

**Rip Cord** ⑧

	200 D
--	-------

**Sheath** ⑨

Material	PVC White - RAL 9016
Diameter	Ø 3.90 ± 0.15 mm

**Mass**

	25 kg/km
--	----------

**Marking of sheath**

Printing with XXX : Quantity in meter still available per reel DDDDD : Date code	Alarme R 4C AWG24 - elbaC 406004 - DDDDD - XXX m
--	---

Color / Process	Yellow / Ink jet
-----------------	------------------

Step	1 m
------	-----

**Electrical characteristics**

Max conductor DC resistance	< 104.5 Ω/km
Rated voltage	30 V
Insulation resistance 20°C	> 200 MΩ.km

**Color table**

Condu.	Colors		RAL
①	Black	●	9005
②	Red	●	3001
③	White	○	9003
④	Green	●	6018

**Meet Standards**

Environment :	European directive 2011/65/EU
Marking :	CE
Fire reaction :	EN 50575:2014/A1:2016

**Thermal characteristics**

CPR fire reaction class	E <sub>ca</sub>
Rated temperature	80°C

**Packaging**

- B1	: 100m / Carton Box
- W5	: 500m / Wooden Drum

**Notes**