OB AY 34 7

Origin - Provenance - Provenienza: C.E.E.

#### **STRUCTURE**

#### **SEAT**

Anatomical support in (11 mm thickness) of beech plywood with threaded metal inserts.

### **BACKREST**

Interior Anatomical support in (8 mm thickness) beech plywood with threaded metal inserts.

### **PADDING SEAT**

Cold injected Polyurethane foam, CFC free, 40 kg/m3 density, 60 mm thickness.

#### **BACKREST**

Cold injected Polyurethane foam, CFC free, 30 kg/m3 density, 30 mm thickness.

#### **UPHOLSTERY**

#### **SEAT**

Symil-leather/Fabric stiched and mounted to the load-bearing support.

#### **BACKREST**

Symil-leather/Fabric stiched completely upholstered backrest.

#### CONNECTION

Seat/backrest through 30x15 oval tube (15/10 thickness), painted with black epoxy powders.

## **MECHANISMS ASYNCHRONE**

**A-Synchro** mechanism manually lockable in all positions, with lever placed under the left part of the seat, adjustable backrest with permanent contact, with lever placed

under the seat behind on the right side, seat elevation with lever placed on the right front side.

## **SEAT HEIGHT ADJUSTMENT**

Through a class 3 gas lift with 200 mm stroke, complying with DIN 4550/4551 standards

#### **BACKREST HEIGHT ADJUSTMENT**

Manually through a side handle, 60 mm stroke.













# **OB AY 347**

Origin - Provenance - Provenienza: C.E.E.

#### **BASE**

5-star base in black nylon reinforced, Ø 650 mm.

### **OPTIONAL**

5-star base in die-cast, brushed aluminium with chromium plated effect  $\varnothing$  650 mm.

## **FEET**


Fixed polypropylene feet,  $\emptyset$  70 mm.

## **OPTIONAL**

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair,  $\varnothing$  50 mm.

## **CASTORS**

Black soft castors with grey rubber for hard floor and wooden.



**DIMENSIONS - INGOMBRI** 

	Dimensions .		
Α	Seat height	Min	540 mm
		Max	740 mm
В	Total height	Min	980 mm
		Max	1180 mm
С	Seat width		390 mm
D	Max total width		640 mm
Ε	Seat depth		410 mm
F	Total depth		640 mm
G	Backrest height		430 mm
G1	Backrest height adjustmer	nt	60 mm
Н	Backrest width		425 mm



WEIGHT	9,60 Kg
VOLUME	0,15 m3
Quantity per Box	N. 1











OB AY 34 9

Origin - Provenance - Provenienza: C.E.E.



#### **STRUCTURE**

#### **SEAT**

Anatomical support in (11 mm thickness) of beech plywood with threaded metal inserts.

#### **BACKREST**

Interior Anatomical support in (8 mm thickness) beech plywood with threaded metal inserts.

### **PADDING**

#### **SEAT**

Cold injected Polyurethane foam, CFC free, 40 kg/m3 density, 60 mm thickness.

#### **BACKREST**

Cold injected Polyurethane foam, CFC free, 30 kg/m3 density, 30 mm thickness.

#### **UPHOLSTERY**

## **SEAT**

Symil-leather/Fabric stiched and mounted to the load-bearing support.

#### **BACKREST**

Symil-leather/Fabric stiched completely upholstered backrest.

#### CONNECTION

Seat/backrest through 30x15 oval tube (15/10 thickness), painted with black epoxy powders.

### **MECHANISMS ASYNCHRONE**

**A-Synchro** mechanism manually lockable in all positions, with lever placed under the left part of the seat, adjustable backrest with permanent contact, with lever placed

under the seat behind on the right side, seat elevation with lever placed on the right front side.

#### **SEAT HEIGHT ADJUSTMENT**

Through a class 3 gas lift with 260 mm stroke, complying with DIN 4550/4551 standards

## **BACKREST HEIGHT ADJUSTMENT**

Manually through a side handle, 60 mm stroke.

## **FOOTREST**

Footrest in nylon fiberglass reinforced, Ø 450 mm, manually adjustable in height by means of a knob.













# **OB AY 34 9**

Origin - Provenance - Provenienza: C.E.E.

#### **BASE**

5-star base in black nylon reinforced, Ø 700 mm.

### **OPTIONAL**

5-star base in die-cast, brushed aluminium with chromium plated effect  $\varnothing$  700 mm.

## **FEET**


Fixed polypropylene feet,  $\emptyset$  70 mm.

## **OPTIONAL**

Castors polypropylene self-braking double castors, complying with EN1335-2 standard, preventing any accidental movement of the chair,  $\varnothing$  50 mm.

## **CASTORS**

Black soft castors with grey rubber for hard floor and wooden.



**DIMENSIONS - INGOMBRI** 

Α	Seat height	Min	630 mm
	Coat Holgin	Max	890 mm
В	Total height	Min	1070 mm
		Max	1330 mm
С	Seat width		420 mm
D	Max total width		700 mm
<u>E</u>	Seat depth		380 mm
F	Total depth		700 mm
G	Backrest height		430 mm
04	De almost le simbt a divistus aut		00
G1	Backrest height adjustment		60 mm
Н	Do akroot width		425 mm
П	Backrest width		425 mm
P	Diameter foot-rest		450 mm
Г	Diameter 100t-165t		450 11111



WEIGHT	10,80 Kg
VOLUME	0,15 m3
Quantity per Box	N. 1









