

The **ZEVATRON TSM 210** is best suitable for lead free alloys.

Drag Soldering Machine TSM 210

Please have a look at our homepage www.zevatron.com You will find detailed information as well as drawings and news.



Technical Data TSM 210 L x B x H (mm) ca. 2200x650x400 Approx. 130 kg Weight Approx. 45 kg Solder capacity Max. temperature Approx. 350 ℃ 3x400 V, 50 Hz Voltage supply Power rating 8,5 kW

User Advantages

- Optimal solder capacity
- Short heating-up time
- No movement in the solder bath
 Conveying speed 0,5 4 m/min
- No wear parts in the solder bath
 Automatic oxide scrapper
- Lowest oxidation, as the solderOptimal adjustment of is not been pumped
- No interference
- User-friendly operating by go-back mode

Technology

- Pc-board dimensions up to 210 x 250 mm

- parameters for fluxing, pre-heating and soldering
- Extremely robust and proved conveying system
- Air vent Ø 100 mm

ZEVATRON Löttechnik GmbH

Lütersheimer Straße 30, D – 34471 Volkmarsen Telefon: +49 - 56 93 - 8 69, Fax: +49 - 56 93 - 3 92


Homepage: www.zevatron.com, E-Mail: info@zevatron.com




The **ZEVATRON TSM 210** is robust, durable and reliable machine for soldering of THT components.

Our Maschines for are best soldering! leadfree

Sectional view





The pc-board goes horizontally about the fluxer and the pre-heating station, is dragged into the solder bath, goes horizontally about the solder and is dragged out of the solder bath. The 7° in and out angle permits an optimal soldering outline.

The parameters for fluxing, air knife, pre-heating and soldering are individually adjustable. Dwell times for pre-heating and in the solder bath are possible.



The conveying system may be switched over for automatic carrier return (GB mode) so that loading and unloading is possible at the same position.

The TSM 210 is ideal for small and medium series with an extremely short heating-up time and low solder requirement.

Partner for professional professional soldering

ZEVATRON Löttechnik GmbH Lütersheimer Straße 30, D – 34471 Volkmarsen Telefon: + 49 - 56 93 - 8 69, Fax: + 49 - 56 93 - 3 92

Homepage: www.zevatron.com, E-Mail: info@zevatron.com