



1



2



3



4



5

**STANDARD EQUIPMENT:**

- 3-point linkage cat. II with hitch cross shaft for width 2,2 m-3,0 m, cat. III with hitch cross shaft for widths from 3,8 m
- Clearance under the frame: 85 cm
- 2 rows of tines with wing coulter
- Tines protection: shear bolt or double spring
- Levelling discs Ø 460 mm with mechanical depth adjustment, mounted on flat springs
- Tubular tiller Ø 540 mm with mechanical depth adjustment
- Hydraulic folding to transport position for the width from 3.8 m (180°)
- Transport width up to 3,0 m

**OPTIONAL EQUIPMENT:**

- Tubular roller Ø 600 mm
- V-Ring roller with scrapers Ø 600 mm

- Packer roller Ø 500 mm
- Packer roller Ø 600 mm
- Flat bar roller Ø 500 mm
- FLEX roller with scrapers Ø 470 mm
- Warning plates with LED lights

Ref. No.	Working width /m/	Number of tines/ discs /pcs/	Power demand /HP/	Weight /kg/
shear bolt protection				
8331	2,2	5 / 4	70-80	780
8332	2,6	6 / 7	80-100	860
8333	3,0	7 / 8	100-140	930
8334	3,8	9 / 10	140-170	1720
8335	4,7	11 / 12	170-200	2000
8336	5,6	13 / 12	200-250	2280
spring protection				
8331A	2,2	5 / 4	70-80	990
8332A	2,6	6 / 7	80-100	1100
8333A	3,0	7 / 8	100-140	1220
8334A	3,8	9 / 10	140-170	2090
8335A	4,7	11 / 12	170-200	2450
8336A	5,6	13 / 12	200-250	2810
Working depth: up to 15cm				