SP90Y

90-ton lifting capacity

Engine model: Cummins NTA855-C360S10

Rated power: 257 kWOperating weight: 55 t

Product features

Delivering ultimate power, lift and value, the SP90Y features a Cummins engine, load feedback, overload prevention, anti-rollover protection and precise controls. Our first offering for larger loads.





SHANTUI VALUE THAT WORKS

Shantui Construction Machinery Co., Ltd.

ADDRESS:


No. 58, G327 Highway Jining City, Shandong, CHINA


TEL: +86-537-2909369 FAX: +86-537-2311219 EMAIL: trade@shantui.com

SP90Y

Technical specifications:

	ONS	Operating weight	55000 kg
	WEIGHT AND DIMENSIONS	Maximum lifting weight	90000 kg
		Track shoe width	860 mm
		Minimum turning radius	3950 mm
		Ground length	3620 mm
Ø;	SERVICE REFILL CAPACITIES	Ground clearance	550 mm
		Fuel tank capacity	640 L
		Hydraulic tank capacity	196 L
		Engine oil	45 L
000	ENGINE	Cooling system	121 L
		Rated power	257 kW
		Model	Cummins NTA855-C360S10
		Piston displacement	14 L
		Stroke-bore × stroke	6–139.7 × 152.4 mm
		Rated revolution	2000 rpm
	TRANSMISSION SYSTEM	Туре	Hydraulic transmission
		Hydraulic torque converter	3-element, 1 stage, 1 phase
		Transmission	Planetary gear, forced lubrication
		Number of track rollers (each side)	9
		Number of carriers (each side)	2
		Travel speed 1st (forward/reverse)	3.6/4.4 km/h
		Travel speed 2nd (forward/reverse)	6.6/7.8 km/h
		Travel speed 3rd (forward/reverse)	11.2/12.9 km/h
*	WORKING PUMP	Туре	Duplex pump
		Displacement of large pump	225 ml/r
		Displacement of small pump	201 ml/r
,	JW.	Rated working pressure	21 MPa
2	PIPELAYING EQUIPMENT	Boom Length	8600 mm
		Max.lifting height	7000 mm
		Boom swing amplitude	1200~7200 mm
		Boom Line speed	6 m/min
		Gradeability	20°
		Ground press	0.0866 MPa





THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.

WWW.**SHANTUI**.COM