



Model		AJ-1600(W)	AJ-2601(W)	AJ-2801(W)	AJ-1600(S)	AJ-2601(S)	AJ-2801(S)
Print Head		Single Head	Double Heads	Single Head	Double Heads	Single Head	Double Heads
Printing Technology		Piezoelectric Inkjet					
Media Width		210-1620mm - 1.6M / 210-1820mm - 1.8M					
Media	Type	Roll or Sheet					
	Thickness	Maximum 1.5mm					
	Roll Weight	25kg			40kg		
Ink Cartridge	Type	Water Based Dye Ink		ECO Solvent Ink			
		Water Based Pigment Ink					
		Sublimation Ink					
	Capacity	220ml / 440ml Refill Cartridge					
Color	Double 4-color (C M Y K)						
Ink Supply		Continuous Ink Supply Cartridge					
Color Gamut Performance		1670 Million Color					
Printing Resolution		Maximum 1440 dpi					
Media Control		Automatic Feeding System and Sheet Cutter					
Media Sensors		Paper Sensor & Width Sensor					
Height of Print Head		1.5mm - 2.5mm		2.0mm - 3.0mm			
Print Head Cleaning		Automatic cleaning and manual cleaning					
Programming Language		RD-RTL,RD-PJL					
Interface		USB2.0/ HIUSB					
Power Requirement	During Operation	100V to 240V±10%,50/ 60 Hz					
	Sleep Mode	100V to 240V±10%,50/ 60 Hz					
Power-saving Function		Automatic Power Saving					
Acoustic Noise Level	During Operation	≤65 dB (according to ISO 7779)					
	During Standby	≤40 dB (according to ISO 7779)					
Package Dimension (with stand)		2680mm(W)x850mm(D)x790mm(H) - 1.6M Printer 2980mm(W)x850mm(D)x890mm(H) - 1.8M Printer					
Weight(with stand)		148kg (1.6M) / 198kg (1.8M)					
Power Consumption		≤1500VA					
Environment	Power On	Temperature: 20 to 32°C Humidity: 35 to 80%RH (non-condensing)					
	Power Off	Temperature: 5 to 40°C Humidity: 20 to 80%RH (non-condensing)					
Accessories		Power Cord, Drain Bottle, Manual					



Extra Plate Dryer



Optional Take Up Device , Enables Unattended Operation !

ECO SOLEVENT PRINTER

SPECIFICATION