

PORTE ENGINES



TP 1802 F

Options:

- Roue de secours + support
- Timon articulé TZ
- Fond de tôle galvanisée
- Treuil de halage
- Porte échelle

TYPE	P.T.C.	P.V.	C.U.	Essieu(x)	Dim. utiles	Dim. hors-tout	Roues
TP 1001 F	1300 kg	350 kg	950 kg	1 x 1300 kg	1.50 x 1.00 m	3.10 x 1.65 m	185 R 14 C
TP 1151 F	1600 kg	500 kg	1100 kg	1 x 1600 kg	3.00 x 1.60 m	4.60 x 2.15 m	185 R 14 C
TP 1102 F	1600 kg	650 kg	950 kg	2 x 900 kg	3.00 x 1.60 m	4.60 x 2.08 m	165 / 70 R 13
TP 1452 F	2000 kg	780 kg	1220 kg	2 x 1100 kg	3.00 x 1.60 m	4.60 x 2.15 m	185 / 70 R 14
TP 1902 F	2500 kg	800 kg	1700 kg	2 x 1300 kg	3.00 x 1.60 m	4.60 x 2.15 m	185 R 14 C
TP 2602 F	3200 kg	800 kg	2400 kg	2 x 1600 kg	3.00 x 1.60 m	4.60 x 2.15 m	185 R 14 C
TP 2852 F	3500 kg	880 kg	2620 kg	2 x 1800 kg	3.00 x 1.60 m	4.60 x 2.20 m	215 R 14 C
TP 1402 F	2000 kg	700 kg	1300 kg	2 x 1100 kg	4.00 x 1.80 m	5.60 x 2.45 m	185 / 70 R 14
TP 1852 F	2500 kg	780 kg	1720 kg	2 x 1300 kg	4.00 x 1.80 m	5.60 x 2.45 m	185 R 14 C
TP 2552 F	3200 kg	780 kg	2420 kg	2 x 1600 kg	4.00 x 1.80 m	5.60 x 2.45 m	185 R 14 C
TP 2802 F	3500 kg	980 kg	2520 kg	2 x 1800 kg	4.00 x 1.80 m	5.60 x 2.50 m	215 R 14 C
TP 2822 F	3500 kg	1100 kg	2400 kg	2 x 2000 kg	4.00 x 1.80 m	5.60 x 2.50 m	215 R 14 C



TPS 1452 F

(Avec option timon réglable)

Options:

- Roue de secours + support
- Timon articulé TZ
- Fond de tôle galvanisée
- Kit location
- Kit assistance à gaz

TYPE	P.T.C.	P.V.	C.U.	Essieu(x)	Dim. utiles	Dim. hors-tout	Roues
TPS 1452 F	2000 kg	680 kg	1320 kg	2 x 1100 kg	3.00 x 1.60 m	4.60 x 2.10 m	185 / 70 R 14
TPS 1902 F	2500 kg	700 kg	1800 kg	2 x 1300 kg	3.00 x 1.60 m	4.60 x 2.10 m	185 R 14 C
TPS 2602 F	3200 kg	700 kg	2500 kg	2 x 1600 kg	3.00 x 1.60 m	4.60 x 2.10 m	185 R 14 C
TPS 2852 F	3500 kg	750 kg	2750 kg	2 x 1800 kg	3.00 x 1.60 m	4.60 x 2.15 m	215 R 14 C
TPS 1402 F	2000 kg	750 kg	1250 kg	2 x 1100 kg	4.00 x 1.80 m	5.60 x 2.45 m	185 / 70 R 14
TPS 1852 F	2500 kg	750 kg	1750 kg	2 x 1300 kg	4.00 x 1.80 m	5.60 x 2.45 m	185 / 70 R 14
TPS 2552 F	3200 kg	750 kg	2450 kg	2 x 1600 kg	4.00 x 1.80 m	5.60 x 2.45 m	185 R 14 C
TPS 2802 F	3500 kg	800 kg	2700 kg	2 x 1800 kg	4.00 x 1.80 m	5.60 x 2.50 m	215 R 14 C